

**Close-coupled pump, three phase, TEFC**

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>230/460 volts (continued)</b>											
20	3600	256JM	<b>EJMM4106T</b>	5,730	PC3	25.30	281	91	230/460	23	1, 30
		256JP	<b>EJPM4106T</b>	5,730	PC3	28.16	264	91	230/460	23	1, 30
	1800	256JM	<b>EJMM2334T</b>	5,780	PC3	25.30	304	93	230/460	24	1, 30
		256JP	<b>EJPM2334T</b>	5,780	PC3	28.16	300	93	230/460	24	1, 30
25	3600	284JM	<b>EJMM4107T</b>	6,513	PC3	26.96	353	91.7	230/460	29	20, 30
		284JP	<b>EJPM4107T</b>	6,513	PC3	29.84	349	91.7	230/460	29	20, 30
	1800	284JM	<b>EJMM4103T</b>	6,746	PC3	28.64	387	93.6	230/460	30	1, 30
		284JP	<b>EJPM4103T</b>	6,746	PC3	31.51	412	93.6	230/460	30	1, 30
30	3600	286JM	<b>EJMM4108T</b>	8,956	PC3	28.64	406	91.7	230/460	33	1, 30
		286JP	<b>EJPM4108T</b>	8,956	PC3	31.51	405	91.7	230/460	35	1, 30
	1800	286JM	<b>EJMM4104T</b>	9,541	PC3	28.64	422	93.6	230/460	36	1, 30
		286JP	<b>EJPM4104T</b>	9,541	PC3	31.51	452	93.6	230/460	36	1, 30
40	3600	324JM	<b>EJMM4109T</b>	10,142	PC3	30.64	487	92.4	230/460	45	1, 30
		324JP	<b>EJPM4109T</b>	10,142	PC3	33.51	498	92.4	230/460	45	1, 30
	1800	324JM	<b>EJMM4110T</b>	11,074	PC3	30.65	586	94.1	230/460	48	1, 30
		324JP	<b>EJPM4110T</b>	11,074	PC3	33.41	602	94.1	230/460	48	1, 30
50	3600	326JM	<b>EJMM4114T</b>	12,319	PC3	30.65	595	93	230/460	56	1, 30
		326JP	<b>EJPM4114T</b>	12,319	PC3	33.41	604	93	230/460	56	1, 30
	1800	326JM	<b>EJMM4115T</b>	12,490	PC3	30.65	624	94.5	230/460	58	1, 30
		326JP	<b>EJPM4115T</b>	12,490	PC3	33.41	646	94.5	230/460	58	1, 30
<b>575 volts</b>											
1	1800	143JM	<b>EJMM3546T-5</b>	1,464	PC3	15.43	38	85.5	575	1.2	1
1 1/2	3600	143JM	<b>EJMM3550T-5</b>	1,444	PC3	15.41	38	84	575	1.5	
	1800	145JM	<b>EJMM3554T-5</b>	1,599	PC3	15.43	41	86.5	575	1.8	1
2	3600	145JM	<b>EJMM3555T-5</b>	1,558	PC3	15.41	41	85.5	575	2	
	1800	145JM	<b>EJMM3558T-5</b>	1,676	PC3	15.43	45	86.5	575	2.3	1
3	3600	145JM	<b>EJMM3559T-5</b>	1,683	PC3	16.29	50	86.5	575	2.9	1
	1800	182JM	<b>EJMM3610T-5</b>	1,874	PC3	16.69	63	86.5	575	2.9	
5	1800	182JM	<b>EJMM3611T-5</b>	1,887	PC3	18.06	70	89.5	575	3.3	1
	3600	184JM	<b>EJMM3613T-5</b>	2,032	PC3	18.06	74	88.5	575	4.7	1
7 1/2	1800	184JM	<b>EJMM3615T-5</b>	1,935	PC3	19.56	93	89.5	575	5.3	1
	3600	184JM	<b>EJMM3616T-5</b>	2,546	PC3	19.56	96	89.5	575	6.8	1
10	1800	213JM	<b>EJMM3710T-5</b>	2,733	PC3	20.88	127	91.7	575	7.6	1, 35
	3600	215JM	<b>EJMM3711T-5</b>	2,995	PC3	19.76	118	90.2	575	9.5	20
15	1800	215JM	<b>EJMM3714T-5</b>	3,015	PC3	22.38	165	91.7	575	9.6	1, 35
	3600	215JM	<b>EJMM3713T-5</b>	4,000	PC3	22.38	169	91	575	13.4	1
20	1800	254JM	<b>EJMM2394T-5</b>	5,325	PC3	23.07	225	91	575	13.5	1, 35
	3600	254JM	<b>EJMM2333T-5</b>	4,973	PC3	25.30	268	92.4	575	14.6	1, 35

(a) See notes on inside back flap.

■ Cast iron frame

Information

General purpose  
Single phase

General purpose  
Three phase

Severe duty

Large Motors  
and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty