

Close-coupled pump, three phase, ODP

Information	Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
	Foot mounted, 230/460 (continued)											
General purpose Single phase	25	3600	256JM	EJMM2516T	5,925	PC3	23.19	219	91.7	230/460	28	1, 30
			256JP	EJPM2516T	5,925	PC3	26.06	230	91.7	230/460	28	1, 30
		1800	284JM	EJMM2531T	5,892	PC3	25.94	317	93.6	230/460	30	1, 30
			284JP	EJPM2531T	5,892	PC3	28.81	335	93.6	230/460	30	1, 30
General purpose Three phase	30	3600	284JM	EJMM2534T	7,015	PC3	26.56	309	91.7	230/460	33	1, 30
			284JP	EJPM2534T	7,015	PC3	29.44	310	91.7	230/460	33	1, 30
		1800	286JM	EJMM2535T	7,110	PC3	25.94	359	94.1	230/460	35	1, 30
			286JP	EJPM2535T	7,110	PC3	28.81	370	94.1	230/460	35	1, 30
Severe duty	40	3600	286JM	EJMM2538T	8,630	PC3	26.56	328	92.4	230/460	45	1, 30
			286JP	EJPM2538T	8,630	PC3	29.44	329	92.4	230/460	45	1, 30
		1800	324JM	EJMM2539T	9,169	PC3	27.44	417	94.1	230/460	49	1, 30
			324JP	EJPM2539T	9,169	PC3	30.31	378	94.1	230/460	47	1, 30
Large Motors and Generators	50	3600	324JM	EJMM2542T	9,597	PC3	26.94	421	93	230/460	58	1, 30
			324JP	EJPM2542T	9,597	PC3	29.81	424	93	230/460	58	1, 30
		1800	326JM	EJMM2543T	9,938	PC3	27.94	491	94.5	230/460	57	1, 30
			326JP	EJPM2543T	9,938	PC3	30.81	500	94.5	230/460	57	1, 30
Washdown duty	60	326JM	EJMM2546T	11,683	PC3	26.94	472	93.6	230/460	68	1, 30	
		364JP	EJPM2547T	12,269	PC3	33.19	565	95	230/460	68	1, 30	
Explosion proof	75	3600	364JM	EJMM2547T	12,269	PC3	33.19	565	95	230/460	68	1, 30
			364JP	EJPM2547T	12,269	PC3	33.19	565	95	230/460	68	1, 30
		1800	365JM	EJMM2551T	14,619	PC3	36.22	597	95	230/460	87	1, 30
			365JP	EJPM2551T	14,619	PC3	36.22	597	95	230/460	87	1, 30
	Foot mounted, 575 volts											
Pump	3	3600	145JM	EJMM3158T-5	1,446	PC3	14.25	48	85.5	575	3	
			182JM	EJMM3211T-5	1,834	PC3	16.50	74	89.5	575	3.1	1
		1800	182JM	EJMM3212T-5	1,729	PC3	16.50	63	90.2	575	4.5	
			184JM	EJMM3218T-5	1,969	PC3	18.00	92	89.5	575	5.2	1
Farm duty	5	3600	184JM	EJMM3219T-5	2,495	PC3	16.50	77	88.5	575	6.9	1
			213JM	EJMM3311T-5	2,824	PC3	18.19	120	91	575	7.4	1, 35
		1800	213JM	EJMM3312T-5	2,921	PC3	19.31	137	91.7	575	9.2	
			215JM	EJMM3313T-5	3,303	PC3	18.19	132	91.7	575	10	1
HVAC	10	3600	215JM	EJMM3314T-5	3,917	PC3	19.31	131	90.2	575	14	1
			215JM	EJMM3314T-5	3,917	PC3	19.31	131	90.2	575	14	1
		1800	143JM	VEJMM3116T	1,164	PC3	14.43	37	85.5	230/460	1.5	1, 30
			145JM	VEJMM3154T	1,248	PC3	15.43	43	86.5	230/460	2.2	1, 30
Footless, 230/460	2	3600	145JM	VEJMM3157T	1,365	PC3	15.43	46	86.5	230/460	2.9	1, 30
			145JM	VEJMM3158T	1,446	PC3	14.25	48	85.5	230/460	3.8	1, 30
		1800	184JM	VEJMM3211T	1,498	PC3	18.06	74	89.5	230/460	4.2	1, 30
			182JM	VEJMM3212T	1,729	PC3	16.66	63	86.5	230/460	6	1, 30
Footless, 575 volts	5	3600	184JM	VEJMM3218T	1,696	PC3	19.56	84	89.5	230/460	6.6	1, 30
			184JM	VEJMM3219T	2,495	PC3	18.04	77	88.5	230/460	8.6	1, 30
		1800	213JM	VEJMM3311T	2,559	PC3	19.78	125	91	230/460	9.6	1, 30
			213JM	VEJMM3312T	2,921	PC3	18.19	121	89.5	230/460	12	1, 30
Footless, 230/460	7 1/2	3600	215JM	VEJMM3313T	2,770	PC3	22.41	165	91.7	230/460	12	1, 30
			215JM	VEJMM3314T	3,917	PC3	18.69	131	90.2	230/460	17.5	1, 30
		1800	143JM	VEJMM3116T-5	1,164	PC3	15.43	44.00	86.5	575	1.1	
			145JM	VEJMM3154T-5	1,248	PC3	16.31	51.00	86.5	575	1.6	
Footless, 575 volts	2	3600	145JM	VEJMM3157T-5	1,365	PC3	16.31	52.00	86.5	575	2.1	
			182JM	VEJMM3211T-5	1,498	PC3	18.06	74.00	89.5	575	3.1	
		1800	184JM	VEJMM3218T-5	1,696	PC3	18.06	77.00	89.5	575	5.2	

(a) See notes on inside back flap.

**ODP motors retain IP rating when mounted in horizontal position only.