

General purpose, single phase, TEFC, foot mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1	3600	56/56H	EL3509	1,047	GE1	12.93	38	74	115/208-230	4.7	12, 65
		56/56H	L3509	818	GE1	12.93	37	68	115/230	5.9	3, 30, 36
		56/56H	L3509M	925	GE1	12.93	40	66	115/230	6	3, 36
	1800	56/56H	L3510A	1,191	GE1	12.91	40	67	115/230	6.5	3, 30, 36
		56/56H	L3510M	1,149	GE1	12.93	38	67	115/230	6.5	3, 30, 36
		56/56H	EL3510	1,355	GE1	13.81	45	82.5	115/230	4.3	1, 36, 65
		56/56H	L3510	958	GE1	12.93	41	68	115/230	6.4	3, 30, 36
		143T	L3510T	978	GE1	13.29	39	68	115/230	6.4	3, 30
		143T	L3510TM	1,149	GE1	13.31	40	67	115/230	6.5	3, 30
		56/56H	L3513	1,097	GE1	12.93	41	70	115/230	8	3, 30, 36
1 1/2	3600	56/56H	L3513M	1,255	GE1	12.91	46	70	115/230	7.5	2, 3, 36
		143T	L3513T	1,075	GE1	13.31	43	70	115/230	8	3, 30
		56/56H	L3514	1,107	GE1	13.81	49	80	115/230	6.2	30, 36, 65
	1800	56/56H	L3514A	1,411	GE1	13.81	48	75.5	115/230	8	2, 36, 65
		56/56H	L3514M	1,298	GE1	13.81	51	75.5	115/208-230	8	2, 36, 65
		56/56H	EL3514	1,543	GE1	15.18	58	84	115/230	6.3	1, 36, 65
		145T	EL3514T	1,543	GE1	15.55	58	84	115/230	6.3	1, 65
		145T	L3514T	1,123	GE1	13.30	44	78.5	115/208-230	7	65
		145T	L3514TM	1,298	GE1	14.17	49	75.5	115/208-230	8	2, 65
		1200	184T	L3613T	2,934	GE1	16.56	77	73	115/230	8.2
2	3600	56/56H	L3515	1,400	GE1	13.79	52	74	115/230	11.5	1, 3, 30, 36
		56/56H	L3515M	1,466	GE1	13.79	52	74	115/230	11.5	2, 3, 36
		145T	L3515T	1,411	GE1	14.19	52	74	115/230	11.5	1, 3, 30
	1800	145T	EL3515T	1,810	GE1	14.18	65	77	115/208-230	8.3	1, 65
		56HZ	L3516TM	1,848	GE1	13.31	46	82.5	208-230	8.1	1, 57
		145T	L3516T	1,793	GE1	14.17	51	78.5	115/230	8.8	1, 65
		182T	L3605T	1,602	GE1	16.56	68	75.5	115/230	11.5	3, 30
		182T	L3605TM	1,955	GE1	16.56	73	75	115/230	11	2, 3
		182T	EL3605T	2,109	GE1	16.56	66	82.5	115/230	8.8	1, 65
		182T	EL3606T	1,969	GE1	16.56	79	82	115/230	12.4	2, 65
3	3600	182T	L3606T	1,655	GE1	16.56	74	76	115/230	14.5	1, 3, 30
		184T	EL3609T	2,462	GE1	18.06	89	85.5	230	11.8	1, 65
		184T	L3609T	1,885	GE1	16.56	80	78	115/230	14	2, 20, 30, 65
	1800	184T	L3609TM	2,040	GE1	16.54	79	78	115/230	14.5	2, 20
		184T	EL3608T	2,714	GE1	18.06	91	85	230	19.4	2, 20, 65
		184T	L3608T	2,276	GE1	18.06	88	83	230	19.5	2, 20, 65
		184T	L3608TM	2,348	GE1	18.05	89	83	230	19.5	2, 20
		184T	EL3612T	2,936	GE1	18.06	97	86.5	230	19.1	2, 20, 65
		184T	L3612TM	1,327	GE1	18.05	100	80	230	23	2, 20
		213T	L3708T	2,251	GE1	19.02	116	84	230	20.5	1, 30, 65
7 1/2	213T	L3708TM	2,643	GE1	19.02	135	82	230	21.5	2, 65	
	3600	213T	L3709T	2,931	GE1	17.89	123	83	230	33	2, 30, 65
	1800	215T	L3710T	2,972	GE1	19.02	134	86.5	230	29	2, 20, 30, 65
10	3600	215T	L3711T	3,593	GE1	19.02	148	82	230	40	2, 20, 65
	1800	215T	L3712T	3,647	GE1	20.52	158	86.5	230	38	2, 20, 65
15	1800	254T	L1177T	10,387	GE1	23.28	323	86.5	230	60	2, 20, 65
		256T	L3912T	9,328	GE1	24.56	303	86.5	208-230	58	

(a) See notes on inside back flap.

■ Cast iron frame

*IP54 when Drain Fitting Kit #HA5027A03 is installed in the weep holes (48 thru 256T frame motors only)