

**General purpose, three phase, totally enclosed, foot mounted**

Hp	RPM	NEMA Frame	Enclosure	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>230/460 volts (continued)</b>												
15	3600	215T	TEFC	<b>EM3713T</b>	3,450	GE3	20.52	172	91	230/460	17	1, 30
		254T	TEFC	<b>EM2394T</b>	4,150	GE3	23.28	241	91	230/460	17.5	1, 30
	1800	254T	TEFC	<b>EM2333T</b>	3,371	GE3	23.28	270	92.4	230/460	18.1	1, 30
	1200	284T	TEFC	<b>EM4100T</b>	6,389	GE3	27.76	391	91.7	230/460	21	1, 30
	900	286T	TEFC	<b>EM2395T</b>	10,651	GE3	27.76	455	89.5	230/460	23	1, 30
20	3600	256T	TEFC	<b>EM4106T</b>	4,555	GE3	23.28	262	91	230/460	23	1, 30
		256T	TEFC	<b>EM2334T-12</b>	5,174	GE3	23.28	291	93	230/460	23	1, 30
	1800	256T	TEFC	<b>EM2334T</b>	4,087	GE3	23.28	289	93	230/460	24	1, 30
	1200	286T	TEFC	<b>EM4102T</b>	8,507	GE3	27.76	399	91.7	230/460	27	1, 30
	900	324T	TEFC	<b>EM4112T</b>	12,111	GE3	30.28	534	90.2	230/460	35	1, 30
25	3600	256T	TEFC	<b>EM4118T</b>	5,312	GE3	23.28	305	91.7	230/460	29	1, 30
		284TS	TEFC	<b>EM4107T</b>	5,943	GE3	24.70	327	91.7	230/460	29	1, 30
	1800	284T	TEFC	<b>EM4103T</b>	5,345	GE3	27.76	388	93.6	230/460	30	1, 30
	1200	284T	TEFC	<b>EM4103T-12</b>	6,926	GE3	27.56	402	93.6	230/460	30	1, 25, 30
	900	326T	TEFC	<b>EM4116T</b>	14,958	GE3	30.28	578	90.2	230/460	37	1, 30
30	3600	286TS	TEFC	<b>EM4108T</b>	7,061	GE3	24.70	347	91.7	230/460	34	1, 30
		286T	TEFC	<b>EM4104T</b>	6,340	GE3	27.76	430	93.6	230/460	38	1, 30
	1800	286T	TEFC	<b>EM4104T-12</b>	8,047	GE3	27.76	425	93.6	230/460	36	1, 25
	1200	326T	TEFC	<b>EM4117T</b>	11,120	GE3	30.28	604	93	230/460	39	1, 30
	900	364T	TEFC	<b>EM4338T</b>	16,635	GE3	33.44	813	92.4	230/460	39.3	1, 30
40	3600	324TS	TEFC	<b>EM4109T</b>	9,677	GE3	28.78	551	92.4	230/460	46	1, 30
		324T	TEFC	<b>EM4110T</b>	8,291	GE3	30.28	570	94.1	230/460	48	1, 30
	1800	324T	TEFC	<b>EM4110T-12</b>	10,743	GE3	30.28	601	94.1	230/460	48	1, 25, 30
	1200	364T	TEFC	<b>EM4308T</b>	13,855	GE3	33.48	899	94.1	230/460	49.4	1, 30
	900	364T	TEFC	<b>EM4348T</b>	20,633	GE3	33.48	875	93	230/460	52	1, 30
50	3600	326TS	TEFC	<b>EM4114T</b>	10,586	GE3	28.78	575	93	230/460	56	1, 30
		326T	TEFC	<b>EM4115T</b>	9,058	GE3	30.28	650	94.5	230/460	58	1, 30
	1800	326T	TEFC	<b>EM4115T-12</b>	11,609	GE3	30.28	652	94.5	230/460	58	1, 25
	1200	326TS	TEFC	<b>EM4115TS</b>	10,208	GE3	28.78	639	94.5	230/460	58	1, 30
	900	365T	TEFC	<b>EM4312T</b>	16,742	GE3	33.48	902	94.1	230/460	61.7	1, 30
60	3600	405T	TEFC	<b>EM4458T</b>	25,336	GE3	38.20	1216	93	230/460	63	1, 30
		364TS	TEFC	<b>EM4310T</b>	14,873	GE3	31.36	810	95	230/460	65.1	1
	1800	364T	TEFC	<b>EM4314T</b>	13,071	GE3	33.48	912	95	230/460	67.8	1, 30
	1200	364T	TEFC	<b>EM4314T-12</b>	16,890	GE3	33.48	850	95	230/460	68	1, 25
	900	364TS	TEFC	<b>EM4314TS</b>	14,687	GE3	31.36	907	95	230/460	68	1, 30
75	3600	404T	TEFC	<b>EM4403T</b>	20,322	GE3	38.04	1187	95	230/460	69	1
		405T	TEFC	<b>EM4468T</b>	29,260	GE3	38.20	1216	93	230/460	76	1
	1800	365TS	TEFC	<b>EM4313T</b>	17,302	GE3	31.36	980	94.5	230/460	80.7	1
	1200	365T	TEFC	<b>EM4316T</b>	15,284	GE3	33.48	955	95.4	230/460	84.9	1, 30
	900	365T	TEFC	<b>EM4316T-12</b>	19,750	GE3	33.48	955	95.4	230/460	85.9	1, 25
100	3600	405T	TEFC	<b>EM4316TS</b>	17,173	GE3	31.36	946	95.4	230/460	85.9	1
		405T	TEFC	<b>EM4404T</b>	23,664	GE3	38.04	1229	94.5	230/460	86.8	1
	1800	405TS	TEFC	<b>EM4402T-4</b>	22,121	GE3	35.04	1187	95	460	110	1, 25
	1200	405T	TEFC	<b>EM4400T</b>	18,927	GE3	38.04	1203	95.4	230/460	112	1
	900	405T	TEFC	<b>EM4400T-12</b>	24,527	GE3	38.04	1211	95.4	230/460	112	1, 25
125	3600	405TS	TEFC	<b>EM4400TS</b>	21,328	GE3	35.04	1206	95.4	230/460	112	1
		444T	TEFC	<b>EM4409T-4</b>	28,561	GE3	44.75	1828	95	460	119	1
	1800	444TS	TEFC	<b>EM4412T-4</b>	27,343	GE3	40.83	1901	95	460	137	1
	1200	444T	TEFC	<b>EM4410T-4</b>	23,541	GE3	44.75	1969	95.4	460	144	1, 25
	900	444T	TEFC	<b>EM4410T-4</b>	26,401	GE3	41.08	2001	95.4	460	144	1
150	3600	444T	TEFC	<b>EM4410TR-4</b>	28,423	GE3	44.75	1988	95.4	460	144	1, 5
		445T	TEFC	<b>EM4411T-4</b>	33,600	GE3	44.75	2073	95	460	146	1, 25
	1800	445TS	TEFC	<b>EM4413T-4</b>	32,173	GE3	41.08	1995	95	460	164	1
	1200	445T	TEFC	<b>EM4406T-4</b>	26,951	GE3	44.75	1826	95.8	460	169	1, 25
	900	445T	TEFC	<b>EM4406TS-4</b>	30,369	GE3	41.08	2071	95.8	460	169	1
150	1200	445T	TEFC	<b>EM4406TR-4</b>	32,392	GE3	44.75	1826	95.8	460	169	1, 5, 25
		447T	TEFC	<b>EM44156T-4</b>	38,486	GE3	48.24	2571	95.8	460	170	1, 25

(a) See notes on inside back flap.

■ Cast iron frame

\*IP54 when Drain Fitting Kit #HA5027A03 is installed in the weep holes (48 thru 256T frame motors only)

**For larger Hp motors, please refer to the "Large Motors and Generators" section of the catalog.**

Information

General purpose  
Single phase

General purpose  
Three phase

Severe duty

Large Motors  
and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty