

General purpose, three phase, open drip proof, foot mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
230/460 volts (continued)												
2	3600	56	EM31155	942	G03	12.07	43	85.5	230/460	2.6	1, 15, 30	
		143T	EM3155T	1,182	G03	11.62	41	85.5	230/460	2.5	1, 30	
		145T	EM3157TA	1,442	G03	12.13	44	86.5	230/460	2.9	1, 30	
	1800	56H	EM31157	1,090	G03	12.63	45	86.5	230/460	3	1, 15, 30	
		145T	EM3157T	1,164	G03	12.12	40	86.5	230/460	2.9	1, 30	
		1200	184T	EM3215T	1,433	G03	16.50	79	87.5	230/460	3.4	1, 30
3	3600	900	213T	EM3303T	2,944	G03	17.45	111	86.5	230/460	3.5	1, 30
		56H	EM31158	1,056	G03	11.75	50	85.5	230/460	3.8	1, 15, 30	
		145T	EM3158T	1,197	G03	13.00	46	85.5	230/460	3.8	1, 30	
	1800	182T	EM3211T	1,255	G03	15.00	69	89.5	230/460	4.2	1, 30	
		182T	EM3211TA	1,545	G03	15.00	65	89.5	230/460	4.4	1, 30	
		1200	213T	EM3305T	1,823	G03	16.32	119	88.5	230/460	4.5	1, 30
5	3600	182T	EM3212T	1,307	G03	13.62	61	86.5	230/460	6	1, 30	
		184T	EM3218T	1,375	G03	16.50	84	89.5	230/460	6.6	1, 30	
		184T	EM3218TA	1,680	G03	16.50	84	89.5	230/460	6.6	1, 30	
	1800	215T	EM3309T	2,389	G03	17.45	139	89.5	230/460	7.4	1, 30	
		900	254T	EM2504T	4,741	G03	23.19	240	88.5	230/460	7.6	1, 30
		3600	184T	EM3219T	2,073	G03	15.00	74	88.5	230/460	8.6	1, 30
7 1/2	1800	213T	EM3311T	2,019	G03	16.32	115	91	230/460	9.7	1, 30	
		1200	254T	EM2506T	2,864	G03	23.19	239	90.2	230/460	11	1, 30
		900	256T	EM2508T	5,933	G03	23.19	260	89.5	230/460	11.7	1, 30
10	3600	213T	EM3312T	2,371	G03	16.32	121	89.5	230/460	12	1, 30	
		1800	215T	EM3313T	2,444	G03	17.45	128	91.7	230/460	12.5	1, 30
		1200	256T	EM2511T	3,726	G03	23.19	255	91.7	230/460	14.3	1, 30
	3600	215T	EM3314T	3,367	G03	16.32	124	90.2	230/460	17.5	1, 30	
		1800	254T	EM2513T	3,460	G03	21.69	211	93	230/460	17.7	1, 30
			254T	EM2513T-CI	3,710	G03	20.63	238	93	230/460	17.8	1, 30
15	1200	284T	EM2524T	5,024	G03	23.81	278	91.7	230/460	20.5	1, 30	
		3600	254T	EM2514T	3,955	G03	21.69	191	91	230/460	23.5	1, 30
		256T	EM2515T	4,276	G03	21.69	225	93	230/460	23.5	1, 30	
	1800	256T	EM2515T-12	4,846	G03	21.69	225	93	230/460	23.5	1, 25, 30	
		256T	EM2515T-CI	4,662	G03	22.38	281	93	230/460	24	1, 30	
		1200	286T	EM2528T	6,114	G03	23.81	302	92.4	230/460	27	1, 30
20	3600	256T	EM2516T	4,749	G03	21.69	222	91.7	230/460	28	1, 30	
		284T	EM2531T	5,213	G03	25.06	331	93.6	230/460	30	1, 30	
		1800	284T	EM2531T-12	6,117	G03	25.06	307	93.6	230/460	30	1, 25, 30
	1800	284T	EM2531T-CI	5,683	G03	23.44	382	93.6	230/460	31	1, 30	
		1200	324T	EM2532T	7,385	G03	27.69	411	93	230/460	34	1, 30
		3600	284TS	EM2534T	5,605	G03	22.44	308	91.7	230/460	35	1, 30
25	3600	286T	EM2535T	5,701	G03	25.06	335	94.1	230/460	35	1, 30	
		1800	286T	EM2535T-12	6,605	G03	25.06	339	94.1	230/460	35	1, 25, 30
		286T	EM2535T-CI	6,213	G03	24.94	240	94.1	230/460	35	1, 30	
	1200	326T	EM2536T	7,703	G03	28.69	380	93.6	230/460	38	1, 30	
		3600	286TS	EM2538T	7,221	G03	22.44	329	92.4	230/460	46	1, 30
		286TS	EM2538T-CI	7,871	G03	23.57	402	92.4	230/460	46	1, 30	
30	1800	324T	EM2539T	7,436	G03	27.19	396	94.1	230/460	49	1, 30	
		324T	EM2539T-12	8,838	G03	27.19	397	94.1	230/460	47	1, 25, 30	
		324T	EM2539T-CI	8,107	G03	26.13	538	94.1	230/460	46	1, 30	
	1200	364T	EM2540T	10,418	G03	29.81	598	94.1	230/460	51	1, 30	
		364T	EM2540T-CI	10,973	G03	29.70	801	94.1	230/460	49.4	1, 30	

(a) See notes on inside back flap.

Cast iron frame

Information

General purpose
Single phase

General purpose
Three phase

Severe duty

Large Motors
and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty