

General purpose, three phase, open drip proof, foot mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
230/460 volts (continued)												
50	3600	324TS	EM2542T	7,864	G03	25.69	394	93	230/460	56	1, 30	
		324TS	EM2542T-CI	8,918	G03	24.62	548	93	230/460	56	1, 30	
	1800	326T	EM2543T	8,205	G03	27.69	467	94.5	230/460	57	1, 30	
		326T	EM2543T-12	9,607	G03	27.69	468	94.5	230/460	61	1, 25, 30	
		326T	EM2543T-CI	8,946	G03	27.63	570	94.5	230/460	57	1, 30	
		326TS	EM2543TS-12	9,607	G03	26.19	469	94.5	230/460	61	1, 25, 30	
	1200	365T	EM2544T	12,582	G03	33.72	762	94.1	230/460	62	1, 30	
		365T	EM2544T-CI	13,285	G03	29.70	722	94.1	230/460	60.3	1, 30	
60	3600	326TS	EM2546T	9,951	G03	25.19	458	93.6	230/460	68	1, 30	
		364T	EM2547T	10,331	G03	30.69	615	95	230/460	68	1, 30	
	1800	364T	EM2547T-12	12,534	G03	30.69	620	95	230/460	68	1, 25, 30	
		364T	EM2547T-CI	11,260	G03	29.70	745	95	230/460	69.5	1, 30	
	1200	364TS	EM2547TS-12	12,534	G03	28.56	613	95	230/460	68	1, 25, 30	
		404T	EM2548T	15,500	G03	34.47	888	94.5	230/460	76	1, 30	
75	3600	404T	EM2548T-4CI	16,865	G03	34.00	1009	95	460	70.4	1	
		364TS	EM2549T	13,051	G03	25.81	502	93.6	230/460	82	1, 30	
	1800	365T	EM2551T	12,681	G03	33.72	744	95	230/460	87	1, 30	
		365T	EM2551T-12	14,884	G03	33.72	758	95	230/460	85	1, 25	
		365T	EM2551T-CI	13,819	G03	29.70	762	95	230/460	86.5	1, 30	
		365TS	EM2551TS-12	14,884	G03	31.59	749	95	230/460	85	1, 25	
	1200	405T	EM2552T-4	18,777	G03	34.00	1067	95	460	86.9	1, 25	
	100	3600	365TS	EM2550T	13,952	G03	27.81	562	93.6	230/460	110	1, 30
			404T	EM2555T	14,752	G03	34.47	930	95.4	230/460	118	1, 30
		1800	404T	EM2555T-12	17,952	G03	36.97	946	95.4	230/460	118	1, 25
404T			EM2555T-4	14,752	G03	36.97	896	95.4	460	115	1, 25	
404T			EM2555T-CI	16,080	G03	34.00	1038	95.4	230/460	115	1, 30	
404TS			EM2555TS-12	17,952	G03	33.97	941	95.4	230/460	118	1, 25	
125	1200	444T	EM2583T-4	20,667	G03	39.56	1455	95	460	116	1, 25	
		404TS	EM2554T-4	17,509	G03	31.85	894	94.1	460	143	1, 25	
	3600	404TS	EM2554T-4CI	20,891	G03	31.00	997	95	460	143	1	
		405T	EM2559T-4	18,099	G03	34.47	955	95.4	460	143	1, 25	
		405T	EM2559T-4CI	19,724	G03	34.00	1118	95.4	460	141	1	
		405TS	EM2559TS-4	18,099	G03	34.97	1238	95.4	460	143	1, 25	
	150	1200	445T	EM2557T-4	22,321	G03	39.71	1513	95	460	146	1, 25
			405TS	EM2556T-4	21,599	G03	31.85	980	94.1	460	166	1, 25
1800		444T	EM2558T-4	20,103	G03	39.71	1528	96.2	460	170	1, 25	
		444TS	EM2558TS-4	20,103	G03	35.96	1519	96.2	460	170	1	
1200		445T	EM2560T-4	26,286	G03	39.71	1572	95.4	460	175	1, 25	
		444TS	EM2562T-4	24,476	G03	35.88	1364	95.4	460	221	1, 25	
200	1800	445T	EM2563T-4	25,122	G03	39.56	1625	95.8	460	222	1, 25	
		447T	EM2564T-4	34,554	G03	43.06	1827	95.4	460	232	1, 25	
	1200	445TS	EM2565T-4	28,713	G03	35.81	1539	95.4	460	274	1, 25	
250	1800	447T	EM25254T-4	28,171	G03	43.06	2036	96.2	460	275	1, 25	
		3600	445TS	EM2568T-4	44,878	G03	35.88	1539	95.8	460	324	1, 25
300	1800	449T	EM25694T-4	42,960	G03	48.06	2151	95.8	460	331	1, 25	
		3600	449TS	EM2571T-4	51,360	G03	44.31	1899	95.4	460	380	1, 25
350	1800	449T	EM2572T-4	50,744	G03	48.12	2694	96.2	460	382	1, 25	
		3600	449TS	EM25402T-4	60,255	G03	44.31	2083	96.2	460	431	1, 25
400	1800	449T	EM25404T-4	55,073	G03	48.12	2799	96.2	460	437	1, 25	
		3600	449TS	EM25452T-4	66,351	G03	44.31	2284	96.2	460	494	1, 25
450	1800	449T	EM25454T-4	62,284	G03	48.12	2888	96.2	460	507	1, 25	

(a) See notes on inside back flap.

■ Cast iron frame