

## Inverter-Duty®

three phase, ODP, C-Face, foot mounted

with internal AEGIS® bearing protection ring 1 thru 100 Hp



**IP22**



### Features:

- Class H insulation for increased protection on inverter use
- Internal grounding ring for bearing current mitigation
- Designed for longevity with 3 year warranty
- Suitable for inverter use per NEMA MG1 Part 31.4.4.2

### Applications:

- Fans
- Pumps
- Blowers
- Unit handling
- HVAC systems
- Variable speed applications
- General purpose applications

Hp	RPM	NEMA Frame	Catalog Number	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>230/460 volt</b>									
1	3600	56C	CEM31115-G	11.75	37	78.5	230/460	1.6	8, 12, 15, 30
	1800	143TC	CEM3116T-G	11.12	34	85.5	230/460	1.5	8, 30
	1200	145TC	CEM3156T-G	11.62	40	82.5	230/460	1.8	8, 30
1 1/2	3600	143TC	CEM3120T-G	11.12	34	84	230/460	2	8, 30
	1800	145TC	CEM3154T-G	11.62	38	86.5	230/460	2.2	8, 30
	1200	182TC	CEM3207T-G	15.00	67	86.5	230/460	2.5	8, 30
2	3600	143TC	CEM3155T-G	11.62	41	85.5	230/460	2.5	8, 30
	1800	145TC	CEM3157T-G	12.12	41	86.5	230/460	2.9	8, 30
	1200	184TC	CEM3215T-G	16.50	79	87.5	230/460	3.4	8, 30
3	3600	145TC	CEM3158T-G	13.00	51	85.5	230/460	3.8	8, 30
	1800	182TC	CEM3211T-G	15.00	72	89.5	230/460	4.2	8, 30
	1200	213TC	CEM3305T-G	16.32	131	88.5	230/460	4.5	8, 30
5	3600	182TC	CEM3212T-G	13.62	63	86.5	230/460	6	8, 30
	1800	184TC	CEM3218T-G	16.50	84	89.5	230/460	6.6	8, 30
	1200	215TC	CEM3309T-G	17.45	141	89.5	230/460	7.4	8, 30
7 1/2	3600	184TC	CEM3219T-G	15.00	75	88.5	230/460	8.6	8, 30
	1800	213TC	CEM3311T-G	16.32	130	91	230/460	9.7	8, 30
	1200	254TC	CEM2506T-G	23.19	243	90.2	230/460	11	8, 30
10	3600	213TC	CEM3312T-G	16.32	121	89.5	230/460	12	8, 30
	1800	215TC	CEM3313T-G	17.45	148	91.7	230/460	12.5	8, 30
	1200	256TC	CEM2511T-G	23.19	255	91.7	230/460	14.3	8, 30
15	3600	215TC	CEM3314T-G	16.32	131	90.2	230/460	17.5	8, 30
	1800	254TC	CEM2513T-G	21.69	251	93	230/460	17.7	8, 30
	1200	284TC	CEM2524T-G	23.81	280	91.7	230/460	20.5	8, 30
20	3600	254TC	CEM2514T-G	21.69	185	91	230/460	23.5	8, 30
	1800	256TC	CEM2515T-G	21.69	250	93	230/460	24	8, 30
	1200	286TC	CEM2528T-G	23.81	299	92.4	230/460	27	8, 30
25	3600	256TC	CEM2516T-G	21.69	233	91.7	230/460	28	8, 30
	1800	284TC	CEM2531T-G	25.06	314	93.6	230/460	30	8, 30
	1200	324TC	CEM2532T-G	27.69	384	93	230/460	34	8, 30
30	3600	284TSC	CEM2534T-G	22.44	320	91.7	230/460	35	8, 30
	1800	286TC	CEM2535T-G	25.06	340	94.1	230/460	35	8, 30
	1200	326TC	CEM2536T-G	28.69	457	93.6	230/460	38	8, 30
40	3600	286TSC	CEM2538T-G	22.44	328	92.4	230/460	46	8, 30
	1800	324TC	CEM2539T-G	27.19	392	94.1	230/460	49	8, 30

(a) See notes on inside back flap.