

General purpose, three phase, totally enclosed, foot mounted

Hp	RPM	NEMA Frame	Enclosure	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
575 volts (continued)												
1 1/2	3600	143T	TEFC	EM3550T-5	1,195	GE3	12.29	36	84	575	1.5	1
	1800	145T	TEFC	EM3554-5	1,199	GE3	13.23	41	86.5	575	1.8	1
		145T	TEFC	EM3554T-5	1,199	GE3	13.31	42	86.5	575	1.8	1
2	1200	182T	TEFC	EM3607T-5	1,629	GE3	16.55	73	87.5	575	1.9	1
	3600	56H	TEFC	EM3555-5	1,309	GE3	12.91	41	85.5	575	2	
		145T	TEFC	EM3555T-5	1,309	GE3	13.29	43	85.5	575	2	1
	1800	56H	TEFC	EM3558-5	1,268	GE3	12.91	45	86.5	575	2.3	1
		145T	TEFC	EM3558T-5	1,268	GE3	13.31	46	86.5	575	2.3	1
	1200	184T	TEFC	EM3614T-5	1,708	GE3	18.05	90	88.5	575	2.8	
3	3600	56H	TEFC	EM3559-5	1,434	GE3	13.79	50	86.5	575	2.9	1
		145T	TEFC	EM3559T-5	1,434	GE3	14.17	60	86.5	575	2.9	1
	1800	182T	TEFC	EM3610T-5	1,452	GE3	15.16	56	86.5	575	2.9	1
		182T	TEFC	EM3611T-5	1,301	GE3	16.55	73	89.5	575	3.3	1
	1800	182T	TEFC	EM3661T-5	1,856	GE3	15.24	97	89.5	575	3.3	1
		1200	213T	TEFC	EM3704T-5	2,221	GE3	19.01	129	89.5	575	3.7
5	3600	184T	TEFC	EM3613T-5	1,610	GE3	16.54	75	88.5	575	4.7	1
	1800	184T	TEFC	EM3615T-5	1,344	GE3	18.05	89	89.5	575	5.3	1
		184T	TEFC	EM3665T-5	1,899	GE3	15.24	108	89.5	575	5.3	1
	1200	215T	TEFC	EM3708T-5	2,510	GE3	19.76	154	89.5	575	5.8	1
7 1/2	3600	184T	TEFC	EM3616T-5	2,124	GE3	18.05	98	89.5	575	6.8	1
		213T	TEFC	EM3709T-5	2,412	GE3	17.89	115	89.5	575	7	1
	1800	213T	TEFC	EM3710T-5	1,938	GE3	19.02	123	91.7	575	7.6	1
		213T	TEFC	EM3770T-5	2,477	GE3	18.45	170	91.7	575	7.5	1
10	3600	215T	TEFC	EM3711T-5	2,445	GE3	17.89	119	90.2	575	9.5	1
	1800	215T	TEFC	EM3714T-5	2,188	GE3	20.52	165	91.7	575	9.6	1
		215T	TEFC	EM3774T-5	2,778	GE3	18.45	185	91.7	575	9.8	1
15	3600	215T	TEFC	EM3713T-5	3,450	GE3	20.52	169	91	575	13.6	1
	1800	254T	TEFC	EM2394T-5	4,150	GE3	23.28	245	91	575	14.1	1
20	3600	254T	TEFC	EM2333T-5	3,371	GE3	23.28	258	92.4	575	14.6	1
		256T	TEFC	EM4106T-5	4,555	GE3	23.28	252	91	575	18.2	1
	1800	256T	TEFC	EM2334T-5	4,087	GE3	23.28	290	93	575	19.2	1
25	3600	284TS	TEFC	EM4107T-5	5,943	GE3	24.70	335	91.7	575	22	1
	1800	284T	TEFC	EM4103T-5	5,345	GE3	27.76	380	93.6	575	24	1
30	3600	286TS	TEFC	EM4108T-5	7,061	GE3	24.70	331	91.7	575	26.5	1
	1800	286T	TEFC	EM4104T-5	6,340	GE3	27.76	408	93.6	575	29	1
40	3600	324TS	TEFC	EM4109T-5	9,677	GE3	28.78	522	92.4	575	37	1
	1800	324T	TEFC	EM4110T-5	8,291	GE3	30.28	575	94.1	575	39	1
50	3600	326TS	TEFC	EM4114T-5	10,586	GE3	28.78	574	93	575	45	1
	1800	326T	TEFC	EM4115T-5	9,058	GE3	30.28	623	94.5	575	46	1
60	1800	364T	TEFC	EM4314T-5	13,071	GE3	33.48	919	95	575	54.4	1
75	1800	365T	TEFC	EM4316T-5	15,284	GE3	33.48	958	95.4	575	68.7	1
100	1800	405T	TEFC	EM4400T-5	18,927	GE3	38.04	1208	95.4	575	89.6	1
125	1800	444T	TEFC	EM4410T-5	23,429	GE3	44.75	1669	95.4	575	115	1
150	1800	445T	TEFC	EM4406T-5	26,951	GE3	44.75	2151	95.8	575	135	1

(a) See notes on inside back flap.

■ Cast iron frame

*IP54 when Drain Fitting Kit #HA5027A03 is installed in the weep holes (48 thru 256T frame motors only)

For larger Hp motors, please refer to the "Large Motors and Generators" section of the catalog.

Information

General purpose
Single phase

General purpose
Three phase

Severe duty

Large Motors
and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty