

Inverter-Duty®, three phase, TEFC, C-Face, foot mounted, with internal AEGIS® bearing protection ring

Hp	RPM	NEMA Frame	Catalog Number	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
230/460 volt continued									
30	3600	286TSC	CEM4108T-G	26.39	336	91.7	230/460	34	8, 30
	1800	286TC	CEM4104T-G	27.76	410	93.6	230/460	38	8, 30
	1200	326TC	CEM4117T-G	30.28	604	93	230/460	39	8, 30
40	3600	324TSC	CEM4109T-G	28.78	532	92.4	230/460	46	8, 30
	1800	324TC	CEM4110T-G	30.28	596	94.1	230/460	48	8, 30
50	3600	326TSC	CEM4114T-G	28.78	584	93	230/460	56	8, 30
	1800	326TC	CEM4115T-G	30.28	648	94.5	230/460	58	8, 30
60	3600	364TSC	CEM4310T-G	31.36	900	95	230/460	66.3	8, 30
	1800	364TC	CEM4314T-G	33.48	907	95	230/460	68	8, 30
75	3600	365TSC	CEM4313T-G	31.36	966	94.5	230/460	81.9	8, 30
	1800	365TC	CEM4316T-G	33.48	956	95.4	230/460	85.9	8, 30
100	1800	405TC	CEM4400T-G	38.20	1214	95.4	230/460	112	8, 30

(a) See notes on inside back flap.

* IP54 when drain fitting kit #HA5027A03 is installed in the weep holes (48 thru 256T frame motors only)

Cast iron frame