

Super-E®, three phase, TEFC, foot mounted, with internal AEGIS® Bearing Protection Ring

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
230/460 volt (continued)											
10	3600	215T	EM3711T-G	2,809	HV3	17.89	118	90.2	230/460	11.8	8,30
	3600	215T	EM3771T-G	3,351	HV3	18.45	164	90.2	230/460	11.8	8,30
	1800	215T	EM3714T-G	2,829	HV3	20.51	156	91.7	230/460	12	8,30
	1800	215T	EM3774T-G	3,140	HV3	18.45	232	91.7	230/460	12.2	8
	1200	256T	EM2332T-G	5,273	HV3	23.30	322	91	230/460	14.1	8,30
15	3600	254T	EM2394T-G	4,632	HV3	23.30	239	91	230/460	17.5	8,30
	1800	254T	EM2333T-G	4,280	HV3	23.30	270	92.4	230/460	18.1	8,30
	1200	284T	EM4100T-G	7,010	HV3	27.76	369	91.7	230/460	21	8,30
20	3600	256T	EM4106T-G	5,037	HV3	23.30	261	91	230/460	23	8,30
	1800	256T	EM2334T-G	5,087	HV3	23.30	295	93	230/460	24	8,30
	1200	286T	EM4102T-G	9,127	HV3	27.76	393	91.7	230/460	27	8,30
25	3600	284TS	EM4107T-G	6,564	HV3	24.70	323	91.7	230/460	29	8,30
	1800	284T	EM4103T-G	6,643	HV3	27.76	400	93.6	230/460	30	8,30
	1200	324T	EM4111T-G	10,376	HV3	30.39	507	93	230/460	32	8,30
30	3600	286TS	EM4108T-G	7,682	HV3	24.70	336	91.7	230/460	34	8,30
	1800	286T	EM4104T-G	7,764	HV3	27.76	410	93.6	230/460	38	8,30
	1200	326T	EM4117T-G	11,871	HV3	30.28	604	93	230/460	39	8,30
40	3600	324TS	EM4109T-G	10,428	HV3	28.78	532	92.4	230/460	46	8,30
	1800	324T	EM4110T-G	10,092	HV3	30.28	596	94.1	230/460	48	8,30
	1200	364T	EM4308T-G	15,139	HV3	33.48	883	94.1	230/460	49.4	8,30
50	3600	326TS	EM4114T-G	11,337	HV3	28.78	584	93	230/460	56	8,30
	1800	326T	EM4115T-G	10,959	HV3	30.28	648	94.5	230/460	58	8,30
	1200	365T	EM4312T-G	18,171	HV3	33.48	910	94.1	230/460	61.7	8,30
60	3600	364TS	EM4310T-G	16,208	HV3	31.36	900	95	230/460	66.3	8,30
	1800	364T	EM4314T-G	16,012	HV3	33.48	907	95	230/460	68	8,30
75	3600	365TS	EM4313T-G	18,759	HV3	31.36	966	94.5	230/460	81.9	8,30
	1800	365T	EM4316T-G	18,624	HV3	33.48	956	95.4	230/460	85.9	8,30
100	1800	405T	EM4400T-G	23,304	HV3	38.20	1214	95.4	230/460	112	8,30
200 volt											
5	1800	184T	EM3665T-8G	2,223	HV3	15.23	119	89.5	200	15.1	8
7 1/2	1800	213T	EM3770T-8G	2,841	HV3	18.45	170	91.7	200	21.4	8
10	1800	215T	EM3774T-8G	3,142	HV3	18.45	231	91.7	200	28	8
15	1800	254T	EM2333T-8G	4,280	HV3	23.30	254	92.4	200	42.4	8
575 volt											
1	1800	143T	EM3546T-5G	1,436	HV3	12.31	35	85.5	575	1.2	8
1 1/2	1800	145T	EM3554T-5G	1,482	HV3	13.31	42	86.5	575	1.8	8
2	1800	145T	EM3558T-5G	1,526	HV3	13.31	46	86.5	575	2.3	8
3	1800	182T	EM3611T-5G	1,708	HV3	16.54	76	89.5	575	3.3	8
5	1800	184T	EM3615T-5G	1,838	HV3	18.04	84	89.5	575	5.3	8
7 1/2	1800	213T	EM3710T-5G	2,547	HV3	19.01	126	91.7	575	7.6	8
10	1800	215T	EM3714T-5G	2,829	HV3	20.51	165	91.7	575	9.6	8
15	1800	254T	EM2333T-5G	4,280	HV3	23.30	250	92.4	575	14.6	8
20	1800	256T	EM2334T-5G	5,087	HV3	23.30	293	93	575	19.2	8
25	1800	284T	EM4103T-5G	6,643	HV3	27.76	364	93.6	575	24	8
30	1800	286T	EM4104T-5G	7,764	HV3	27.76	423	93.6	575	29	8
40	1800	324T	EM4110T-5G	10,092	HV3	30.28	576	94.1	575	39	8
50	1800	326T	EM4115T-5G	10,959	HV3	30.28	644	94.5	575	46	8

(a) See notes on inside back flap.

■ Cast iron frame

*IP54 when drain fitting kit #HA5027A03 is installed in the weep holes (48 thru 256T frame motors only)

Information

General purpose
Single phase

General purpose
Three phase

Severe duty

Large Motors
and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty