

## Fan and blower, single and three phase, ODP, resilient base

1/4 thru 2 Hp

IP22



### Features:

- Resilient cushion base for low noise and reduced vibration
- Terminal panel for ease of connectivity
- Automatic thermal overload protection
- Lubed for life double shielded bearings

### Applications:

- Fans
- Pumps
- Blowers
- Condensers
- Air handling
- HVAC systems
- General purpose applications

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>Single phase</b>											
1/4	1800	48	<b>ERL1203A</b>	514	HV1	10.34	20	68.5	115/230	1.3	13, 30, 96
	3600	48	<b>RL1209A</b>	548	HV1	10.96	27	74	115/230	4.2	12, 30, 96
1/2	1800	56	<b>RL1304A</b>	715	HV1	11.59	26	62	115/230	4.2	12, 30, 66, 96
		56	<b>RL1323A</b>	650	HV1	10.97	24	62	115/230	4	2, 66
3/4	3600	56	<b>ERL1306A</b>	756	HV1	11.59	26	76.2	115/230	3.3	12, 30, 66, 96
		56H	<b>RL1307A</b>	876	HV1	12.96	34	68	115/230	5.1	12, 30, 66, 96
1	1800	56	<b>RL1324A</b>	705	HV1	12.47	31	71	115/230	5	2, 66
		56H	<b>ERL1309A</b>	869	HV1	11.42	36	82	115/230	3.9	12, 30, 66, 96
1 1/2	3600	56H	<b>RL1310A</b>	952	HV1	12.04	34	68	115/230	6.5	12, 30, 66
		56H	<b>ERL1313A</b>	1,135	HV1	13.30	52	82	115/230	5.9	15, 30, 66
1 1/2	1800	56H	<b>ERL1319A</b>	1,275	HV1	14.67	59	83.8	115/230	6.2	15, 66
		<b>Single phase, 277 volt</b>									
1/3	1800	56	<b>RL1301A277</b>	734	HV1	10.97	23	60	277	2.5	13, 66
1/2	1800	56	<b>RL1304A277</b>	764	HV1	11.59	26	62	277	3.6	12, 66
3/4	1800	56H	<b>RL1307A277</b>	1,052	HV1	12.47	34	66	277	4.2	12, 66
1	1800	56H	<b>RL1310A277</b>	1,082	HV1	12.42	42	70	277	5.4	66
1 1/2	1800	56H	<b>ERL1319A277</b>	1,275	HV1	14.67	59	84	277	5.2	15, 66
<b>Three phase</b>											
1/4	1800	48	<b>ERM3003</b>	720	HV3	10.34	21	69.5	230/460	0.5	13, 15, 30
		48	<b>ERM3007</b>	749	HV3	10.34	24	73.4	230/460	0.7	13, 15, 30
1/3	1800	56	<b>ERM3104</b>	749	HV3	10.97	24	73.4	230/460	0.7	13, 15, 30
		48	<b>ERM3009</b>	790	HV3	10.34	24	73.4	230/460	0.8	12, 15, 30
1/2	1800	48	<b>ERM3010</b>	805	HV3	11.84	31	78.2	230/460	0.8	12, 15, 30
		56	<b>ERM3108</b>	805	HV3	11.97	31	78.2	230/460	0.8	12, 15, 30
3/4	3600	56	<b>ERM3111</b>	799	HV3	10.97	24	76.8	230/460	1.2	12, 15, 30
		1800	56	<b>ERM3112</b>	888	HV3	11.42	38	84	208-230/460	1.3
1	3600	56	<b>ERM3115</b>	843	HV3	12.47	27	77	230/460	1.6	12, 15, 30
		1800	56	<b>ERM3116</b>	925	HV3	11.42	37	83.5	230/460	1.45
1 1/2	3600	56H	<b>ERM3120</b>	894	HV3	11.42	34	84	208-230/460	2	15
		1800	56H	<b>ERM3154</b>	955	HV3	12.42	41	86.5	208-230/460	2.2
2	3600	56H	<b>ERM3155</b>	1,037	HV3	12.42	43	85.5	230/460	2.6	15
		1800	56H	<b>ERM3157</b>	1,108	HV3	12.42	43	86.5	208-230/460	2.9

(a) See notes on inside back flap.