

Close-coupled pump, three phase, ODP

1 thru 75 Hp

IP23



Features:

- Rodent screens to protect against trash debris
- Oversize ball bearings for the pump industry
- Locked DE bearing to allow mounting in any configuration**
- Designed for longevity with a 3 year warranty on premium efficient Super-E® Motors
- Suitable for Inverter use per NEMA MG1 Part 31.4.4.2

Applications:

- General purpose pumps
- Industrial applications
- Commercial pumps
- Food and beverage
- Wastewater
- Agricultural
- Aggregate

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Foot mounted, 230/460											
1	1800	143JM	EJMM3116T	1,164	PC3	13.75	38	85.5	230/460	1.5	1, 30
		143JP	EJPM3116T	1,419	PC3	16.81	38	85.5	230/460	1.5	1, 30
1 1/2	3600	143JM	EJMM3120T	1,256	PC3	13.75	34	84	230/460	2	1, 30
		145JM	EJMM3154T	1,260	PC3	13.75	38	86.5	230/460	2.2	1, 30
	1800	145JP	EJPM3154T	1,472	PC3	16.81	37	86.5	230/460	2.2	1, 30
		145JM	EJMM3155T	1,431	PC3	13.75	44	85.5	230/460	2.5	1, 30
2	1800	145JM	EJMM3157T	1,378	PC3	14.25	44	86.5	230/460	2.9	1, 30
		145JP	EJPM3157T	1,559	PC3	17.31	43	86.5	230/460	2.9	1, 30
	3600	145JM	EJMM3158T	1,564	PC3	15.13	49	85.5	230/460	3.8	1, 30
		145JP	EJPM3158T	1,446	PC3	17.31	48	85.5	230/460	3.8	1, 30
3	1800	182JM	EJMM3211T	1,525	PC3	16.50	72	89.5	230/460	4.2	1, 30
		182JP	EJPM3211T	1,834	PC3	19.56	74	89.5	230/460	4.2	1, 30
	3600	182JM	EJMM3212T	1,864	PC3	15.12	64	86.5	230/460	6	1, 30
		182JP	EJPM3212T	1,729	PC3	18.18	63	86.5	230/460	6	1, 30
5	1800	182TCZ	EWCM3212T	1,691	PC3	18.32	63	86.5	230/460	6	1, 30
		184JM	EJMM3218T	1,724	PC3	18.00	87	89.5	230/460	6.6	1, 30
	1800	184JP	EJPM3218T	1,969	PC3	21.06	92	89.5	230/460	6.6	1, 30
		1200	215JM	EJMM3309T	2,939	PC3	19.31	141	89.5	230/460	7.4
	3600	184JM	EJMM3219T	2,203	PC3	16.50	78	88.5	230/460	8.6	1, 30
		184JP	EJPM3219T	2,495	PC3	19.56	77	88.5	230/460	8.6	1, 30
7 1/2	1800	184TCZ	EWCM3219T	2,457	PC3	19.69	77	88.5	230/460	8.6	1, 30
		213JM	EJMM3311T	2,824	PC3	18.19	120	91	230/460	9.7	1, 30
	1800	213JP	EJPM3311T	2,824	PC3	20.94	130	91	230/460	9.3	1, 30
		1200	254JM	EJMM2506T	4,039	PC3	24.69	248	90.2	230/460	11
	3600	213JM	EJMM3312T	2,921	PC3	18.19	120	89.5	230/460	12	1, 30
		213JP	EJPM3312T	2,921	PC3	22.07	122	89.5	230/460	12	1, 30
10	1800	213TCZ	EWCM3312T	2,864	PC3	21.25	121	89.5	230/460	12	1, 30
		215JM	EJMM3313T	2,796	PC3	19.31	136	91.7	230/460	12.5	1, 30
	1200	215JP	EJPM3313T	2,796	PC3	23.20	138	91.7	230/460	12.5	1, 30
		215JM	EJMM2511T	4,902	PC3	24.69	255	91.7	230/460	14.3	1, 30
	3600	215JP	EJPM3314T	3,917	PC3	18.19	131	90.2	230/460	17.5	1, 30
		215TCZ	EWCM3314T	3,860	PC3	21.25	131	90.2	230/460	17.5	1, 30
15	1800	254JM	EJMM2513T	4,135	PC3	23.19	214	93	230/460	17.7	1, 30
		254JP	EJPM2513T	4,135	PC3	26.06	219	93	230/460	17.7	1, 30
	1200	284JM	EJMM2524T	6,434	PC3	24.69	300	91.7	230/460	20.5	1, 30
		3600	254JM	EJMM2514T	4,599	PC3	23.19	195	91	230/460	23.5
20	1800	254JP	EJPM2514T	4,599	PC3	26.06	220	91	230/460	23.5	1, 30
		256JM	EJMM2515T	4,953	PC3	23.19	248	93	230/460	23.5	1, 30
		256JP	EJPM2515T	4,953	PC3	26.06	236	93	230/460	23.5	1, 30

(a) See notes on inside back flap.

**ODP motors retain IP rating when mounted in horizontal position only.

Information

General purpose Single phase

General purpose Three phase

Severe duty

Large Motors and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty