

Information

Auger drive, single phase, TEFC, flange mount, capacitor start

1/3 thru 1 1/2 Hp

IP44**Features:**

- Mechanically protected centrifugal switch from over speeding
- Extended opposite DE shaft for manual jog
- Gasketed manual reset thermal overload protection
- Lubed for life double shielded ball bearings
- NEMA 56N flange for industry standard drive/gear connection

Applications:

- Poultry feed auger drive systems

General purpose
Single phaseGeneral purpose
Three phase

Severe duty

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1/3	1800	48YZ	ANFL3501M	904	FD1	12.44	24	60	115/230	3	12, 30
1/2	1800	48YZ	ANFL3504M	1,014	FD1	12.44	28	68	115/230	3.7	12, 30
3/4	1800	48YZ	ANFL3507M	1,182	FD1	13.32	34	74	115/230	4.1	12, 30
1	1800	56YZ	ANFL3510M	1,459	FD1	13.55	41	67	115/230	6.5	30
1 1/2	1800	56YZ	ANFL3514M	2,165	FD1	14.43	49	75.5	115/230	9	2, 30

(a) See notes on inside back flap.

Large Motors
and Generators

Washdown duty

Grain stirring, single phase, TEFC, foot mounted

1 1/2 Hp

IP44**Features:**

- Slotted fan cover on DE to prevent clogging
- Gasketed manual reset thermal overload protection
- Lubed for life double shielded ball bearings

Applications:

- Inside bin grain stirring systems

Explosion proof

Pump

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1 1/2	1800	56Z	GSL3509M	1,278	FD1	12.29	41	80	208-230	6.4	

(a) See notes on inside back flap.

HVAC

Farm duty