

Pump Motor

Jet pump, single phase, ODP 1/3 thru 3 Hp

IP23



Features:

- Automatic thermal overload protection
- Corrosion resistant stainless steel shaft extension
- Slotted opposite DE shaft for easy installation
- Superior switch design provides optimized torque profiles
- Optimized airflow design providing higher horsepower in a smaller package

Applications:

- HVAC pumps
- Swimming pool pumps
- General purpose pumps

Hp	RPM	NEMA Frame	Catalog Number	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Foot mounted									
1/3	3600	56J	CJL1205A	11.91	23	58	115/230	3.1	
	1800	56J	CJL1301A	11.89	23	60	115/208-230	3	30
1/2	3600	56J	CJL1303A	12.51	30	66	115/230	3.7	
	1800	56J	CJL1304A	12.14	25	62	115/230	4.2	30
3/4	3600	56J	CJL1306A	13.39	30	69	115/230	5.5	
	1800	56J	CJL1307A	12.25	35	63	115/230	5.4	
1	3600	56J	CJL1309A	13.89	32	65	115/208-230	7	30
1 1/2	3600	56J	CJL1313A	13.89	37	78.5	115/230	6.5	
2	3600	56J	CJL1317A	13.25	45	70	115/230	13	30
Footless									
1/3	3600	56J	JL1205A	11.89	25	58	115/230	3.1	
	1800	56J	JL1301A	11.89	23	60	115/230	3	30
1/2	3600	56J	JL1303A	12.51	26	66	115/230	3.7	
	1800	56J	JL1304A	12.14	25	62	115/230	4.2	30
3/4	3600	56J	JL1306A	13.39	33	69	115/230	5.5	
	1800	56J	JL1307A	13.89	33	68	115/230	5.1	30
1	3600	56J	JL1309A	13.89	32	65	115/230	7	30
1 1/2	3600	56J	JL1313A	13.89	36	78.5	115/230	6.5	
2	3600	56J	JL1317A	13.25	45	70	115/230	13	30
3	3600	56J	JL1323A	14.13	52	82.5	230	13	30

(a) See notes on inside back flap.

All threaded shaft, single phase motors are connected single rotation - CCW when viewing drive end.

All above ratings can be UL 1081 compliant through MOD Express®.

See M30A in the MOD Express program section of this catalog for more details.