

Pump motor

Close-coupled pump, three phase, totally enclosed, foot mounted 1 thru 20 Hp

IP55



Features:

- Oversized, double sealed ball bearings
- Locked DE bearing
- Neoprene gaskets
- Lip and V-Ring seal on DE
- NEMA Premium® efficiency
- White epoxy, corrosion resistant finish
- 300 series stainless steel hardware and shaft extension

Applications:

- Water pumps commercial and industrial
- Wet environment

Hp	RPM	NEMA Frame	Enclosure	Catalog Number	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1	3600	143JM	TENV	JMEWDM3545T	15.41	35	84	230/460	1.4	1
	1800	143JM	TENV	JMEWDM3546T	14.25	39	85.5	230/460	1.5	1, 30
1 1/2	3600	143JM	TENV	JMEWDM3550T	14.28	48	85.5	208-230/460	2	1, 30
	1800	145JM	TENV	JMEWDM3554T	15.16	50	86.5	230/460	2.1	30
2	3600	145JM	TEFC	JMEWDM3555T	15.43	47	85.5	208-230/460	2.5	1, 30
	1800	145JM	TEFC	JMEWDM3558T	16.34	48	86.5	230/460	2.9	1, 30
3	3600	145JM	TEFC	JMEWDM3559T	16.31	50	86.5	230/460	3.6	1, 30
	1800	182JM	TEFC	JMEWDM3611T	18.05	70	89.5	230/460	4.2	1, 30
5	3600	184JM	TEFC	JMEWDM3613T	18.05	81	88.5	230/460	5.6	1, 30
		184JM	TEFC	JMEWDM3613T-5	18.05	74	88.5	575	4.7	10
	1800	184JM	TEFC	JMEWDM3615T	19.55	93	89.5	230/460	6.7	1, 30
7 1/2	3600	184JM	TEFC	JMEWDM3616T	19.55	96	89.5	230/460	8.4	1, 30
	1800	213JM	TEFC	JMEWDM3710T	20.91	151	91.7	230/460	9.5	1, 30
10	3600	215JM	TEFC	JMEWDM3711T	20.91	130	90.2	208-230/460	10.8	1, 30
	1800	215JM	TEFC	JMEWDM3714T	22.41	165	91.7	230/460	12	1, 30
15	3600	215JM	TEFC	JMEWDM3713T	21.64	169	91	230/460	17	1, 30
	1800	254JM	TEFC	JMEWDM23933T	25.06	252	92.4	230/460	18	1, 30
20	3600	256JM	TEFC	JMEWDM41906T	25.06	255	91	230/460	23	2
	1800	256JM	TEFC	JMEWDM23934T	25.06	275	93	230/460	24	1, 30

(a) See notes on inside back flap.