

Close-coupled pump, single phase

3 thru 10 Hp

TEFC
IP44

ODP
IP23



Features:

- Oversize ball bearings for the pump industry
- Locked DE bearing to allow mounting in any configuration**
- Dynamically balanced rotor to reduce noise and increase bearing life
- Superior switch design provides optimized torque profiles

Applications:

- Industrial pumps
- General purpose pumps
- Food and beverage
- Wastewater
- Agricultural
- Aggregate
- Cement

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Totally enclosed fan cooled, mechanical seal, Type JM											
3	3600	182JM	JML3606T	1,833	PC1	18.06	79	76	115/230	14.5	1, 30
5	3600	184JM	JML3608T	2,442	PC1	19.55	93	83	230	19.5	2, 20
Open drip proof, mechanical seal, Type JM											
3	3600	182JM	JML1406T	1,749	PC1	16.50	69	78	115/208-230	14	
	1800	184JM	JML1408T	2,004	PC1	16.50	80	78	115/230	16	30
5	3600	184JM	JML1409T	2,468	PC1	16.50	81	80	230	21.5	1, 30
	1800	213JM	JML1508T	2,844	PC1	18.19	115	77	230	27	
7 1/2	3600	213JM	JML1509T	3,540	PC1	18.19	116	81	230	37	30
	1800	215JM	JML1510T	3,745	PC1	19.31	142	85.5	230	31	30
10	3600	215JM	JML1511T	4,354	PC1	19.31	141	83	230	46	20, 30
	1800	215JM	JML1512T	4,635	PC1	20.95	150	84	230	41	20, 30
Open drip proof, packed pump, Type JP											
3	3600	182JP	JPL1406T	1,749	PC1	19.57	76	78	115/230	14	30
	1800	184JP	JPL1408T	2,004	PC1	19.57	87	78	115/230	16	30
5	3600	184JP	JPL1409T	2,468	PC1	19.57	88	80	230	21.5	1, 30
	1800	213JP	JPL1508T	2,844	PC1	22.07	117	77	230	27	
7 1/2	3600	213JP	JPL1509T	3,540	PC1	22.07	121	81	230	37	30
	1800	215JP	JPL1510T	3,745	PC1	23.19	143	85.5	230	31	30
10	3600	215JP	JPL1511T	4,354	PC1	23.19	148	83	230	46	20, 30
	1800	215JP	JPL1512T	4,635	PC1	20.95	142	84	230	41	20, 30
Open drip proof, west coast fit, Type TCZ											
3	3600	182TCZ	WCL1406T	1,760	PC1	19.69	81	78	115/230	14	30
	1800	184TCZ	WCL1408T	2,019	PC1	19.69	91	78	115/230	16	30
5	3600	184TCZ	WCL1409T	2,491	PC1	19.69	91	75	230	23	1, 30
	1800	213TCZ	WCL1508T	2,868	PC1	21.25	116	77	230	27	
7 1/2	3600	213TCZ	WCL1509T	3,563	PC1	21.25	117	81	230	37	30
10	3600	215TCZ	WCL1511T	4,395	PC1	22.38	143	83	230	46	20, 30

(a) See notes on inside back flap.

**ODP motors retain IP rating when mounted in horizontal position only.