

General purpose, single phase, ODP, foot mounted

1/6 thru 10 Hp

IP22



Features:

- Low noise vibration dampening base
- Dynamically balanced rotor to increase bearing life
- Superior switch design provides optimized torque profiles
- Robust heavy gauge steel design
- Optimized airflow design providing higher horsepower in a smaller package

Applications:

- Air handling
- Material handling
- Machine tools
- Conveyors
- Pumps
- Fans

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1/6	1800	48	L1200	494	G01	9.13	18	49	115/230	1.9	30
	1200	48	L1201	757	G01	9.38	23	47	115/230	2.3	30
1/4	1800	48	EL11203	678	G01	9.76	19	68.5	115/230	1.3	15
		48	EL11203M	723	G01	9.76	19	68.5	115/230	1.3	15
	1200	48	EL11204	809	G01	9.76	25	64	115/230	1.5	15
		56	EL11300	841	G01	10.13	25	64	115/230	1.5	15
	3600	48	EL11205	716	G01	9.76	24	70.5	115/230	1.5	15
		48	EL11206	729	G01	9.76	27	72.4	115/230	1.7	15
1/3	1800	48	EL11206M	774	G01	9.76	27	72.4	115/230	1.7	15
		56	EL11301	729	G01	10.13	27	72.4	115/230	1.7	15
	1200	48	EL11207	863	G01	9.76	27	68	115/230	1.9	15
		56	EL11302	863	G01	10.13	30	68	115/230	1.9	15
	3600	48	EL11208	762	G01	9.76	24	72.4	115/230	2.5	15
		56	EL11303	762	G01	10.13	24	72.4	115/230	2.5	15
1/2	1800	48	EL11209	818	G01	10.63	32	76.2	115/230	2.4	15
		48	EL11209M	863	G01	10.63	32	76.2	115/230	2.2	15
	56H	48	EL11304	818	G01	11.00	32	76.2	115/230	2.4	15
		56	EL11304A	863	G01	11.00	32	76.2	115/230	2.3	15
	1200	56H	EL11305	1,296	G01	11.75	46	76.2	115/230	2.2	15
		56H	EL11306	797	G01	11.00	39	76.2	115/230	3.3	15
3/4	3600	56	EL11306A	841	G01	11.00	39	76.2	115/230	3.3	15
		56H	EL11307	975	G01	12.07	39	81.8	115/230	3.5	15
	1800	56	EL11307A	1,019	G01	12.07	39	81.8	115/230	3.4	15
		56	EL11307M	1,019	G01	12.07	39	81.8	115/230	3.4	15
	1200	56H	EL11308	1,459	G01	12.62	47	80.2	115/230	3.1	15
		56H	EL11309	935	G01	12.07	43	82	115/230	3.9	15
1	3600	56	EL11309A	978	G01	12.07	43	82	115/230	3.9	15
		56H	EL11318	1,123	G01	11.75	44	82.6	115/230	4.2	15
	1800	56H	EL11318M	1,166	G01	11.75	44	82.6	115/230	4.5	15
		143T	L1318T	995	G01	12.12	43	67	115/230	6.2	30
	143T	143T	L1318TM	1,037	G01	12.12	42	67	115/230	6.2	2
		56H	EL11313	1,062	G01	12.62	52	82	115/230	5.9	15
1 1/2	3600	56H	EL11313A	1,107	G01	12.62	52	82	115/230	5.9	15
		143T	L1313T	942	G01	11.12	36	70	115/230	8.9	30
	56H	56H	EL11319	1,337	G01	14.00	59	83.8	115/230	6.2	15
		56H	EL11319M	1,446	G01	14.00	59	83.8	115/230	6.2	15
	1800	145T	EL1319T	1,485	G01	13.00	50	85.5	115/208-230	6.3	1, 65
		145T	L1319T	1,060	G01	12.12	42	68	115/230	9	30
145T	L1321T	1,273	G01	13.00	49	70	115/230	10.5	30		
145T	L1321TM	1,382	G01	13.00	48	70	115/208-230	10.5			

(a) See notes on inside back flap.