

General purpose, single phase, TEFC, foot mounted

1/12 thru 15 Hp

IP44*



Features:

- Low noise vibration dampening base
- Dynamically balanced rotor to increase bearing life
- Superior switch design provides optimized torque profiles
- Robust heavy gauge steel design

Applications:

- Air handling
- Material handling
- Machine tools
- Conveyors
- Pumps
- Fans

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1/12	1800	42	L3351	525	GE1	9.56	15	44	115/230	1	3, 30
	3600	42	L3352	537	GE1	9.56	15	45	115/230	1.3	3, 30
1/8	1800	42	L3353	547	GE1	9.56	16	47	115/230	1.6	3, 30
	3600	42	L3354	563	GE1	9.56	16	52	115/230	1.6	3, 30
1/6	1800	42	L3355	596	GE1	9.56	18	51	115/230	1.8	3, 30
		48	L3400	594	GE1	10.72	18	49	115/230	1.9	3, 30
	1200	48	L3401	837	GE1	10.72	23	47	115/230	2.3	3, 30
1/4	3600	42	L3356	603	GE1	9.56	18	57	115/230	2	3, 30
		48	EL3403	744	GE1	11.35	24	74	115/230	1.3	1, 13, 65
	1800	48	L3403	609	GE1	10.72	20	55	115/230	2.5	3, 30
		48	L3403M	698	GE1	10.72	11	55	115/230	2.5	3, 30
	1200	48	L3404	891	GE1	11.34	25	48	115/230	3.2	3, 30
		56	L3500	935	GE1	12.25	30	52.5	115/230	2.6	3, 30
1/3	3600	48	L3405	555	GE1	10.72	21	55	115/208-230	3	3
		48	L3406	647	GE1	10.72	22	60	115/230	3	3, 30
		48	L3406M	734	GE1	10.72	22	60	115/230	3	3, 30
	1800	56	EL3501	822	GE1	11.97	27	77	115/230	1.6	1, 13, 65
		56	L3501	626	GE1	11.34	22	60	115/230	3	3, 30
		56	L3501M	734	GE1	11.34	22	60	115/230	3	3, 30
1/2	1200	48	L3407	980	GE1	11.34	27	54	115/230	3.7	3, 30
		56	L3502	980	GE1	11.97	28	54	115/230	3.7	3, 30
		48	L3408	627	GE1	10.73	22	66	115/230	3.5	3, 30
	3600	56	EL3503	807	GE1	11.97	23	68	115/230	2.5	12, 65
		56	L3503	627	GE1	11.35	23	66	115/230	3.5	3, 30
		48	L3409	718	GE1	11.34	26	68	115/230	3.7	3, 30
3/4	1800	48	L3409M	863	GE1	11.34	26	68	115/230	3.7	3, 30
		56	EL3504	970	GE1	11.97	30	78.5	115/230	2.3	1, 12, 65
		56	L3504	734	GE1	11.35	27	68	115/230	3.7	3, 30
	1200	56	L3504A	878	GE1	11.97	27	68	115/230	3.7	3, 30
		56	L3504M	863	GE1	11.97	27	68	115/230	3.7	3, 30
		56/56H	L3505	1,388	GE1	12.91	43	62.5	115/230	3.9	3, 30, 36
3/4	3600	56	EL3506	907	GE1	11.97	29	72	115/230	3.9	12, 65
		56	L3506	706	GE1	11.97	28	66	115/230	4.8	3, 30
		56	EL3507	1,179	GE1	13.25	44	82.5	115/208-230	3.2	1, 12, 65
	1800	56	L3507	845	GE1	12.47	33	72	115/230	4.2	30, 65
		56	L3507A	1,059	GE1	12.47	35	74	115/230	4.1	30, 65
		56	L3507M	1,013	GE1	12.47	33	74	115/230	4.1	30, 65
1200	56/56H	L3508	1,607	GE1	12.93	44	73.5	115/230	3.9	2, 30, 36, 65	
	143T	L3508T	1,581	GE1	13.29	46	73.5	115/230	3.9	2, 30, 65	

(a) See notes on inside back flap.

*IP54 when Drain Fitting Kit #HA5027A03 is installed in the weep holes (48 thru 256T frame motors only)

Information

General purpose Single phase

General purpose Three phase

Severe duty

Large Motors and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty