

## U-frame, single phase

1 thru 3 Hp

IP54



### Features:

- Ball bearings
- Heavy-gauge steel and cast-iron frames
- Exxon Polyrex™ EM grease
- U-Frame mounting dimensions

### Applications:

- Pumps
- Compressors
- Fans
- Conveyors
- Machine tools

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>Totally enclosed, foot mounted</b>											
1	1200	184	<b>L3607</b>	3,106	DPL	15.69	74	67	115/230	7	1, 3
2	1800	184	<b>L3605</b>	2,371	DPL	15.69	67	75.5	115/230	11.5	1, 3, 30
	1200	215	<b>L3703</b>	5,128	DPL	17.51	113	80	115/230	9.4	2, 30, 65
3	1800	215	<b>L3705</b>	4,043	DPL	17.51	117	80	115/230	14	1, 30, 65
<b>Totally enclosed, C-Face, footless</b>											
2	1800	184C	<b>VL3605</b>	2,557	DPL	15.68	64	75.5	115/230	11.5	1, 3, 30

(a) See notes on inside back flap.