

Three phase, two speed, ODP, foot mounted

1/2 thru 25 Hp

IP22



Features:

- Dual speed ratings
- High performance ball bearings
- Dynamically balanced rotor
- Heavy duty steel or cast-iron frame

Applications:

- Fans
- Blowers
- Pumps

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Voltage	Full Load Amps	Notes (a)
Variable torque, one winding										
1/.25	1800/900	143T	M1004T	1,446	DP2	11.12	33	208-230	3	1
1.5/.38	1800/900	145T	M1005T	1,503	DP2	12.13	38	208-230	4.4	1
2/.5	1800/900	145T	M1006T	1,736	DP2	12.13	41	230	6.1	1
3/.75	1800/900	184T	M1007T	1,864	DP2	13.62	56	208-230	8	1
5/1.3	1800/900	184T	M1008T	2,244	DP2	15.00	71	230	13.2	1
7.5/1.9	1800/900	215T	M1009T	3,206	DP2	16.32	113	230	20	1, 10
10/2.5	1800/900	215T	M1010T	3,634	DP2	17.45	133	208-230	25	1, 10
Variable torque, one winding, 460V										
1/.25	1800/900	143T	M1204T	1,446	DP2	11.12	33	460	1.5	1
1.5/.38	1800/900	145T	M1205T	1,503	DP2	12.13	37	460	2.2	1
2/.5	1800/900	145T	M1206T	1,736	DP2	12.13	41	460	3.1	1
3/.75	1800/900	184T	M1207T	1,864	DP2	13.62	56	460	4	1
5/1.3	1800/900	184T	M1208T	2,244	DP2	15.00	72	460	6.6	1
7.5/1.9	1800/900	215T	M1209T	3,206	DP2	16.32	112	460	10	1
10/2.5	1800/900	215T	M1210T	3,634	DP2	17.45	132	460	13	1
15/3.8	1800/900	254T	M1211T	5,105	DP2	21.69	206	460	20	1
20/5	1800/900	256T	M1212T	6,256	DP2	21.69	204	460	26	1
25/6.3	1800/900	284T	M1213T	7,341	DP2	23.81	330	460	34	1, 10
Variable torque, two windings										
.75/.33	1800/1200	56	M1019	1,553	DP2	12.07	36	230	2.8	
1/.44	1800/1200	145T	M1020T	1,673	DP2	12.13	41	230	3	1, 10
1.5/.67	1800/1200	182T	M1021T	2,027	DP2	13.62	55	208-230	4.4	1, 10
2/.89	1800/1200	182T	M1022T	2,312	DP2	15.00	64	230	5.8	1, 10
3/1.3	1800/1200	184T	M1023T	2,692	DP2	15.00	72	230	8	1
5/2.2	1800/1200	215T	M1024T	4,143	DP2	16.32	113	230	12.8	1, 10
Variable torque, two windings, 460V										
.5/.22	1800/1200	56	M1218	1,479	DP2	11.07	33	460	0.9	
.75/.33	1800/1200	56	M1219	1,553	DP2	12.07	36	460	1.4	1, 10
1/.44	1800/1200	145T	M1220T	1,673	DP2	12.13	41	460	1.9	
1.5/.67	1800/1200	182T	M1221T	2,027	DP2	13.62	55	460	2.2	1, 10
2/.89	1800/1200	182T	M1222T	2,312	DP2	15.00	65	460	3	1
3/1.3	1800/1200	184T	M1223T	2,692	DP2	15.00	72	460	4	1
5/2.2	1800/1200	215T	M1224T	4,143	DP2	16.32	113	460	6.4	1
7.5/3.3	1800/1200	256T	M1225T	5,510	DP2	22.25	148	460	9.9	1
10/4.4	1800/1200	256T	M1226T	6,223	DP2	22.25	172	460	12.7	1, 10
15/6.7	1800/1200	284T	M1227T	7,550	DP2	23.81	345	460	17.9	1, 10
20/8.9	1800/1200	286T	M1228T	10,125	DP2	23.81	330	460	24	1, 10

(a) See notes on inside back flap.