

Pressure washer, single phase, TEFC and ODP

1 1/2 thru 5 Hp

ODP
IP22

TEFC
IP54



Features:

- Manual thermal overload
- Capacitor start, capacitor run
- 1 1/2 horsepower designs rated at 14 amps or less on 115 volts
- UL and CSA recognized component approval

Applications:

- Pressure washers
- Steam cleaners

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Totally enclosed fan cooled											
2	3600	56	PL3515M	1,327	DPS	13.23	42	77	115/230	8.8	1
	1800	56HZ	L3516TM	1,848	DPS	13.31	46	82.5	208-230	8.1	1, 57
3	3600	56	PL3519M	1,456	DPS	14.12	50	78	230	12.5	30
	1800	184T	L3609TM	2,040	DPS	16.54	79	78	115/230	14.5	2, 20
5	3600	184T	L3608TM	2,348	DPS	18.05	89	83	230	19.5	2, 20
	1800	184T	L3612TM	1,327	DPS	18.05	100	80	230	23	2, 20
Totally enclosed fan cooled, C-Face											
1 1/2	3600	56C	PCL3513M	1,174	DPS	13.25	38	75.5	115/230	6.6	
	1800	56C	PCL3514M	1,531	DPS	14.12	54	82.5	115/230	6	1
2	3600	56C	PCL3515M	1,393	DPS	13.24	43	77	115/230	8.8	1
	1800	145TC	CL3516TM	1,862	DPS	14.16	53	82.5	208-230	7.9	1
3	3600	56C	PCL3519M	1,526	DPS	14.12	52	78	230	12.5	30
	1800	184TC	CL3619TM	2,422	DPS	16.54	81	81.5	230	13.2	2, 20
5	3600	184TC	CL3608TM	2,625	DPS	18.05	92	83	230	19.5	2, 20
	1800	184TC	CL3612TM	2,539	DPS	18.05	102	80	230	23	2, 20
Open drip proof											
2	1800	56	EPL1322M	1,466	DPS	14.32	66	84.5	115/230	8.2	1, 96
3	1800	184T	L1408TM	1,696	DPS	15.00	74	78	115/230	16	
5	3600	56/56H	PL1327M	1,414	DPS	13.81	56	74.2	230	23	2, 20, 30, 36, 98
	1800	184T	L1410TM	2,063	DPS	16.50	85	82.5	230	23	30
Open drip proof, C-Face											
2	1800	56C	EPCL1322M	1,619	DPS	14.32	66	84.5	115/230	8.2	1, 96
3	1800	184TC	CL1408TM	1,792	DPS	15.00	80	78	115/230	16	
5	3600	56HCY	PCL1327M	1,490	DPS	14.11	57	74.2	230	23	2, 20, 30, 36, 47, 98
	1800	184TC	CL1410TM	2,160	DPS	16.50	88	82.5	230	23	30

(a) See notes on inside back flap.