

## Three phase, ODP

1/3 thru 5 Hp

IP22



### Features:

- Terminal panel for ease of connectivity
- Automatic thermal overload protection
- Lubed for life double shielded bearings

### Applications:

- Fans
- Pumps
- Blowers
- Condensers
- Air handling
- HVAC systems
- General purpose applications

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>Foot mounted</b>											
5	1800	184T	<b>EHM3218TA</b>	1,772	HV3	16.50	84	89.5	230/460	6.6	11, 30
<b>Resilient base</b>											
1/3	1800	48	<b>RM3007A</b>	529	HV3	10.34	21	68	230/460	0.8	12, 30
1/2	1800	56H	<b>RM3108A</b>	802	HV3	10.97	25	72	230/460	0.9	12, 30, 36
3/4	1800	56H	<b>RM3112A</b>	863	HV3	11.59	32	74	230/460	1.5	12, 30, 36, 96
1	1800	56H	<b>RM3116A</b>	899	HV3	12.47	32	78.5	230/460	2	30, 36, 96
1 1/2	1800	56H	<b>RM3154A</b>	955	HV3	12.04	34	78.5	208-230/460	2.4	36
2	1800	56H	<b>RM3157A</b>	1,095	HV3	12.42	40	81.5	208-230/460	2.9	36
3	3600	145TY	<b>ERM3158TA</b>	1,312	HV3	13.64	48	85.5	230/460	3.8	30
5	3600	145TY	<b>ERHM3162TA</b>	1,874	HV3	15.02	60	86.5	230/460	6.1	30

(a) See notes on inside back flap.

## (PSC) – direct drive fan, single phase, foot mounted, TEAO

1/4 thru 1/2 Hp

IP44\*



### Features:

- 1" extended through bolts for grille mounting
- Terminal panel for ease of connectivity
- Automatic thermal overload protection
- Lubed for life double shielded bearings
- Switchless design for increased reliability

### Applications:

- Fans
- Pumps
- Blowers
- Condensers
- Air handling
- HVAC systems
- General purpose applications

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1/4	1800	48Z	<b>PSC3413A</b>	659	HV1	11.34	19	65.5	115/230	1.3	2, 29
1/3	1800	48Z	<b>PSC3416A</b>	731	HV1	11.34	21	62	115/230	1.8	2, 29
1/2	1800	48Z	<b>PSC3524A</b>	802	HV1	11.96	24	65	115/230	3	2, 29

(a) See notes on inside back flap.

\*IP54 when Drain Fitting Kit #HA5027A03 is installed in the weep holes (48 thru 256T frame motors only)