

XEX severe duty, three phase, totally enclosed, 230/460 volts, 460 and 575 volts, C-Face

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
C-Face, Foot Mounted (continued)												
40	3600	324TSC	CECP4109T	12,183	SDM	28.78	571	92.4	230/460	45	1	
	1800	324TC	CECP4110T	10,847	SDM	30.28	628	94.1	230/460	48	1, 30	
	1200	364TC	CECP4308T	16,493	SDM	33.44	908	94.1	230/460	49.4	1	
50	3600	326TSC	CECP4114T	12,699	SDM	28.78	639	93	230/460	56	1, 30	
	1800	326TC	CECP4115T	12,482	SDM	30.28	656	94.5	230/460	58	1, 30	
	1200	365TC	CECP4312T	19,248	SDM	33.44	908	94.1	230/460	61.7	1	
60	3600	364TSC	CECP4310T	17,464	SDM	31.31	874	95	230/460	65.1	1	
		364TC	CECP4314T	17,287	SDM	33.44	880	95	230/460	68	1	
	1800	364TC	CECP4314T-4	16,631	SDM	33.48	961	95	460	70	1	
75		364TC	CECP4314T-5	16,631	SDM	33.48	961	95	575	55	1	
	3600	365TSC	CECP4313T	19,783	SDM	31.31	899	94.5	230/460	80.7	1	
	1800	365TC	CECP4316T	19,660	SDM	33.44	905	95.4	230/460	85.9	1	
100	3600	405TSC	CECP4402T-4	24,946	SDM	35.31	1327	95	460	110	1	
	1800	405TC	CECP4400T-4	25,036	SDM	38.20	1388	95.4	460	112	1	
125	1800	444TC	CECP4410T-4	30,072	SDM	44.75	2002	95.4	460	144	1	
150	1800	445TC	CECP4406T-4	34,673	SDM	44.75	2138	95.8	460	169	1	
200	1800	447TC	CECP4407T-4	41,710	SDM	48.24	2455	96.2	460	222	1	
C-Face, Footless												
1	3600	56C	VECP3580-4	1,573	SDM	14.50	60	84	460	1.4	1	
		56C	VECP3581	1,720	SDM	14.50	66	87.5	230/460	1.5	1	
		56C	VECP3581-4	1,720	SDM	14.50	66	87.5	460	1.5	1	
		143TC	VECP3581T	1,720	SDM	14.57	67	87.5	230/460	1.5	1	
		143TC	VECP3581T-4	1,720	SDM	14.57	66	87.5	460	1.5	1	
1 1/2	1200	145TC	VECP3582T	1,894	SDM	14.57	69	82.5	230/460	1.7	1	
		3600	143TC	VECP3583T-4	1,775	SDM	14.57	67	85.5	460	2	1
1 1/2	1800	145TC	VECP3584T	1,748	SDM	14.57	71	88.5	230/460	2.1	1	
		145TC	VECP3584T-4	1,748	SDM	14.57	70	88.5	460	2.1	1	
		1200	182TC	VECP3667T	2,249	SDM	16.98	103	87.5	230/460	2.5	1
2	3600	145TC	VECP3586T-4	1,858	SDM	14.57	74	86.5	460	2.5	1	
		145TC	VECP3587T	1,820	SDM	14.57	75	88.5	230/460	2.8	1	
		145TC	VECP3587T-4	1,820	SDM	14.57	75	88.5	460	2.8	1	
		1200	184TC	VECP3664T	2,281	SDM	16.98	114	88.5	230/460	3.2	1
		3600	182TC	VECP3660T-4	2,230	SDM	16.98	103	88.5	460	3.4	1
3	1800	182TC	VECP3661T	2,337	SDM	16.98	112	89.5	230/460	4.1	1	
		182TC	VECP3661T-4	2,337	SDM	16.98	105	89.5	460	4.1	1	
		1200	213TC	VECP3764T	3,364	SDM	21.36	165	90.2	230/460	4.5	1, 30
5	3600	184TC	VECP3663T-4	2,715	SDM	16.98	108	89.5	460	5.7	1	
		184TC	VECP3665T	2,378	SDM	16.98	119	89.5	230/460	6.5	1	
		1800	184TC	VECP3665T-4	2,378	SDM	16.98	119	89.5	460	6.6	1
		1200	215TC	VECP3768T	3,403	SDM	21.36	225	90.2	230/460	7.3	1, 30
		3600	213TC	VECP3769T-4	3,636	SDM	21.36	173	91.7	460	8.6	1
7 1/2	1800	213TC	VECP3770T	3,090	SDM	21.36	170	91.7	230/460	9.5	1	
		213TC	VECP3770T-4	3,090	SDM	21.36	170	91.7	460	9.5	1	
		1200	254TC	VECP2276T	5,332	SDM	27.40	338	91	230/460	10.7	1, 30
10	3600	215TC	VECP3771T-4	3,851	SDM	21.36	203	92.4	460	11	1	
		1800	215TC	VECP3774T	3,650	SDM	21.36	231	92.4	230/460	12.5	1
		215TC	VECP3774T-4	3,650	SDM	21.36	231	92.4	460	12.5	1	
		1200	256TC	VECP2332T	6,674	SDM	27.40	348	91	230/460	14.2	1, 30
15	1800	254TC	VECP2333T	5,154	SDM	27.40	314	92.4	230/460	18.1	1, 30	
		254TC	VECP2333T-4	5,154	SDM	27.40	303	92.4	460	18.1	1	
		1200	284TC	VECP4100T	7,869	SDM	30.68	503	91.7	230/460	21	1, 30
20	1800	256TC	VECP2334T	5,464	SDM	27.40	338	93	230/460	24	1, 30	
		256TC	VECP2334T-4	5,464	SDM	27.40	365	93	460	24	1	
		1200	286TC	VECP4102T	10,270	SDM	30.68	528	91.7	230/460	27	1
25	1800	284TC	VECP4103T	7,234	SDM	30.68	483	93.6	230/460	31	1, 30	
		1200	324TC	VECP4111T	10,809	SDM	33.03	636	93	230/460	32	1, 30

(a) See notes on inside back flap.

■ Cast iron frame