

General purpose, single phase, ODP, C-Face

1/6 thru 5 Hp

IP22



Features:

- Locked DE bearing to allow mounting in any configuration**
- Low noise vibration dampening base
- Dynamically balanced rotor to increase bearing life
- Superior switch design provides optimized torque profiles
- Robust heavy gauge steel design
- Optimized airflow design providing higher horsepower in a smaller package

Applications:

- Gear reducers
- Material handling
- Machine tools
- Conveyors
- Pumps
- Fans

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
C-Face, foot mounted											
1/3	1800	56C	CEL11301	779	G01	10.74	27	72.4	115/230	1.7	15
	3600	56C	CEL11303	812	G01	10.74	24	72.4	115/230	2.5	15
1/2	1800	56C	CEL11304	868	G01	11.62	32	76.2	115/230	2.4	15
	3/4	1800	56C	CEL11307	1,024	G01	12.06	39	81.8	115/230	3.5
1	1800	56C	CEL11310	1,172	G01	12.06	44	82.6	115/230	4.2	15
3	1800	184TC	CL1408TM	1,792	G01	14.99	80	78	115/230	16	
5	1800	184TC	CL1410TM	2,160	G01	16.49	88	82.5	230	23	1, 30
C-Face, footless, drip cover											
1/6	1800	56C	KL1200	530	G01	11.22	19	49	115/230	1.9	30
1/4	1800	56C	KEL11203	728	G01	11.85	22	68.5	115/230	1.3	15
		56C	KEL11205	766	G01	11.85	24	70.5	115/230	1.5	15
1/3	3600	56C	KEL11205A	810	G01	12.66	24	70.5	115/230	1.5	15
		56C	VEL11301	779	G01	11.85	27	72.4	115/230	1.7	15
	1800	56C	VEL11301A	823	G01	11.85	27	72.4	115/230	1.7	15
		56C	VEL11303	812	G01	11.85	24	72.4	115/230	2.5	15
1/2	3600	56C	VEL11303A	823	G01	11.85	24	72.4	115/230	2.5	15
		56C	VEL11304	868	G01	12.73	32	76.2	115/230	2.4	15
	1800	56C	VEL11304A	912	G01	12.51	32	76.2	115/230	2.3	15
		56C	VEL11305	1,345	G01	13.24	42	76.2	115/230	2.2	15
3/4	3600	56C	VEL11306	846	G01	14.04	39	76.2	115/230	3.3	15
		56C	VEL11306A	891	G01	14.04	39	76.2	115/230	3.3	15
	1800	56C	VEL11307	1,024	G01	13.22	44	81.8	115/230	3.5	15
		56C	VEL11307A	1,069	G01	12.75	39	81.8	115/230	3.4	15
	1200	56C	VEL11308	1,508	G01	14.12	47	80.2	115/230	3.1	15
		56C	VEL11309	985	G01	12.06	43	82	115/230	3.9	15
1	3600	56C	VEL11309A	1,029	G01	12.06	43	82	115/230	3.9	15
		56C	VEL11318	1,172	G01	13.24	44	82.6	115/230	4.2	15
	1800	56C	VEL11318A	1,217	G01	12.75	44	82.6	115/230	4.2	15
		56C	VEL11313	1,113	G01	14.10	52	82	115/230	5.9	15, 30
1 1/2	3600	56C	VEL11313A	1,158	G01	14.10	52	82	115/230	5.9	15
		56C	VEL11319	1,386	G01	15.50	59	83.8	115/230	6.2	15
2	1800	145TC	VL1321T	1,311	G01	14.17	48	70	115/230	10.5	30
		56C	VEL11317	1,223	G01	15.47	66	82.9	115/230	7.8	15
	3600	56C	VEL11317A	1,268	G01	15.47	66	82.9	115/230	7.8	15
		1800	145TC	VL1322T	1,335	G01	14.18	49	75.5	115/230	10.2
3	3600	182TC	VL1406T	1,622	G01	15.18	61	75.5	115/230	13.6	30, 65
		1800	184TC	VL1408T	1,642	G01	16.55	78	78	115/230	16

(a) See notes on inside back flap.

**ODP motors retain IP rating when mounted in horizontal position only.