

**P-base vertical solid shaft pump, three phase, TEFC**

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>Medium thrust (continued)</b>											
20	3600	256LP	<b>VLECP4106T</b>	10,096	PV3	25.73	265	92.4	230/460	22	1
	1800	256LP	<b>VLECP2334T</b>	9,332	PV3	25.73	303	93	230/460	24	1
25	3600	284LP	<b>VLECP4107T</b>	12,266	PV3	32.44	396	91.7	230/460	28	1
	1800	286LP	<b>VLECP4103T</b>	11,864	PV3	32.44	420	93.6	230/460	30	1
30	3600	286LP	<b>VLECP4108T</b>	13,743	PV3	32.44	446	91.7	230/460	34	1
	1800	286LP	<b>VLECP4104T</b>	13,053	PV3	32.44	460	94.1	230/460	36	1
40	3600	324LP	<b>VLECP4109T</b>	18,199	PV3	34.72	528	93.6	230/460	45	1
	1800	324LP	<b>VLECP4110T</b>	16,758	PV3	34.72	600	94.5	230/460	46	1
<b>High thrust</b>											
50	3600	326VP	<b>VPECP4114T</b>	18,851	PV3	34.71	587	93	230/460	56	1
	1800	326VP	<b>VPECP4115T</b>	18,581	PV3	34.71	700	94.5	230/460	58	1
60	3600	364VP	<b>VPECP4310T</b>	25,548	PV3	37.25	999	95	230/460	65.1	1
	1800	364VP	<b>VPECP4314T</b>	23,873	PV3	37.25	910	95	230/460	68	1
75	3600	365VP	<b>VPECP4313T</b>	27,573	PV3	37.25	1005	94.5	230/460	80.7	1
	1800	365VP	<b>VPECP4316T</b>	26,485	PV3	37.25	965	95.4	230/460	85.9	1

(a) See notes on inside back flap.  
 ■ Cast iron frame

Information

General purpose Single phase

General purpose Three phase

Severe duty

Large Motors and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty