

Information

Stainless steel, three phase, totally enclosed, C-Face, footless 1/3 thru 10 Hp

IP56

General purpose
Single phase

General purpose
Three phase



Features:

- 300 series stainless steel motor frame, endplates, conduit box, shaft, base, and hardware
- Four condensate drains in each endplate
- Endplate rabbets sealed
- Labyrinth seals on DE and ODE
- 3 year warranty

Applications:

- Food processing
- Packaging
- Pumps and wastewater
- Wet environment

Severe duty

Large Motors
and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty

Hp	RPM	NEMA Frame	Enclosure	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
230/460 volt												
1/3	3600	56C	TENV	VSSWDM3457	1,685	WDS	11.09	33	74	208-230/460	0.6	1, 10, 30
	1800	56C	TENV	VSSWDM3534	1,775	WDS	11.09	35	75.5	208-230/460	0.7	1,10,12,30
1/2	3600	56C	TENV	VSSWDM3537	2,001	WDS	11.09	37	70	208-230/460	0.9	2, 10, 30
	1800	56C	TEFC	VSSFWDM3538	2,277	WDS	12.34	40	80	208-230/460	0.9	1,10,12,30
3/4		56C	TENV	VSSWDM3538	2,154	WDS	11.09	40	84	230/460	0.9	1, 10, 12, 30
	1	3600	56C	TENV	VSSWDM3541	2,078	WDS	11.09	41	80	230/460	1.1
1800		56C	TEFC	VSSFWDM3542	2,351	WDS	12.34	44	82.5	208-230/460	1.1	1, 10
	1	56C	TENV	VSSWDM3542	2,233	WDS	11.09	42	82.5	208-230/460	1.1	1, 10
1		56C	TENV	VESSWDM3546	2,254	WDS	12.09	44	85.5	230/460	1.5	1,30
	1	56C	TEFC	VESSFWDM3546	2,485	WDS	13.34	39	85.5	230/460	1.5	
1 1/2		143TC	TEFC	VESSWDM3546T	2,289	WDS	13.42	44	87.5	230/460	1.5	1,30
	1800	56C	TEFC	VESSWDM3554	2,299	WDS	13.34	46	86.5	230/460	2.2	1,30
2		145TC	TEFC	VESSWDM3554T	2,333	WDS	13.42	45	87.5	230/460	2.1	1,30
	1800	56C	TEFC	VESSWDM3558	2,781	WDS	13.34	48	86.5	230/460	2.8	8, 30
3		145TC	TEFC	VESSWDM3558T	2,816	WDS	13.42	45	86.5	230/460	2.8	8, 30
	5	3600	145TC	TEFC	VESSWDM3559T	3,346	WDS	15.67	64	86.5	208-230/460	3.7
10		1800	182TC	TEFC	VESSWDM3611T	3,213	WDS	18.32	60	89.5	230/460	4.2
	7 1/2	3600	184TC	TEFC	VESSWDM3613T	3,761	WDS	18.32	83	90.2	230/460	5.7
10		1800	184TC	TEFC	VESSWDM3615T	3,634	WDS	18.32	101	89.5	230/460	6.5
	10	1800	213TC	TEFC	VESSWDM3710T	4,601	WDS	20.16	139	91.7	230/460	9.5
10		1800	215TC	TEFC	VESSWDM3714T	5,088	WDS	21.66	188	92.4	230/460	12.5
	575 volt											
1	1800	56C	TENV	VESSWDM3546-5	2,254	WDS	12.09	39	85.5	575	1.2	
1 1/2	1800	145TC	TEFC	VESSWDM3554T-5	2,333	WDS	13.42	45	87.5	575	1.7	1
	3600	56C	TEFC	VESSWDM3555-5	2,725	WDS	14.22	41	86.5	575	2.0	1
2	1800	145TC	TEFC	VESSWDM3558T-5	2,816	WDS	15.67	56	88.5	575	2.2	8
	3	1800	182TC	TEFC	VESSWDM3611T-5	3,213	WDS	18.32	83	89.5	575	3.3
5	1800	184TC	TEFC	VESSWDM3615T-5	3,634	WDS	18.32	112	89.5	575	5.1	1
	10	1800	215TC	TEFC	VESSWDM3714T-5	5,088	WDS	21.66	191	92.4	575	10.1

(a) See notes on inside back flap.
Red catalog number indicates **NEW** product.