

Information

Single phase, totally enclosed, foot mounted

1/2 thru 1 1/2 Hp

IP55**Features:**

- 300 series stainless steel hardware
- Neoprene gaskets
- Double sealed ball bearings
- Lip and V-Ring seal on DE
- White epoxy, corrosion resistant finish
- Stainless steel shaft extension

Applications:

- Food processing
- Wet environment
- Packaging
- Pumps and wastewater

General purpose
Single phaseGeneral purpose
Three phase

Severe duty

Hp	RPM	NEMA Frame	Enclosure	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1/2	1800	56	TEFC	WDL3504	1,024	WDW	12.23	34	68	115/230	3.7	1, 12, 30
3/4	1800	56	TEFC	WDL3507	1,199	WDW	12.23	37	68	115/230	5.5	1, 12, 30
1	1800	56	TEFC	WDL3510	1,386	WDW	13.23	41	67	115/230	6.4	1, 30
1 1/2	1800	145T	TEFC	WDL3514T	1,708	WDW	14.18	50	80	115/230	6.2	1, 30

(a) See notes on inside back flap.

Large Motors
and Generators

Washdown duty

Single phase, totally enclosed, C-Face

1/2 thru 1 1/2 Hp

IP55**Features:**

- 300 series stainless steel hardware
- Neoprene gaskets
- Double sealed ball bearings
- Lip and V-Ring seal on DE
- White epoxy, corrosion resistant finish
- Stainless steel shaft extension

Applications:

- Food processing
- Wet environment
- Packaging
- Pumps and wastewater

Explosion proof

Pump

Hp	RPM	NEMA Frame	Enclosure	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Foot mounted												
1/2	1800	56C	TEFC	CWDL3504	1,072	WDW	12.23	35	68	115/230	3.7	1, 12, 30
3/4	1800	56C	TEFC	CWDL3507	1,248	WDW	12.23	36	68	115/230	5.5	1, 12, 30
1	3600	56C	TEFC	CWDL3509	1,169	WDW	12.23	37	68	115/230	5.9	1, 12, 30
	1800	56C	TEFC	CWDL3510	1,434	WDW	13.23	41	67	115/230	6.4	1, 30
1 1/2	3600	56C	TEFC	CWDL3513	1,444	WDW	13.23	41	70	115/230	8	1, 30
	1800	56C	TEFC	CWDL3514	1,717	WDW	14.12	50	80	115/230	6.2	1, 30
Footless												
1/2	1800	56C	TEFC	VWDL3504	1,028	WDW	12.25	35	68	115/230	3.7	1, 12, 30
3/4	1800	56C	TEFC	VWDL3507	1,207	WDW	12.25	36	68	115/230	5.5	1, 12, 30
1	1800	56C	TEFC	VWDL3510	1,382	WDW	13.25	42	67	115/230	6.4	1, 30
1 1/2	1800	56C	TEFC	VWDL3514	1,658	WDW	14.10	48	80	115/230	6.2	1, 30

(a) See notes on inside back flap.

HVAC

Farm duty