

Yoke/pedestal fan, single phase, PSC, TEAO

1/4 thru 1/2 Hp

IP54



Features:

- Robust stamped steel pedestal mount
- 1" extended through bolts for grille mounting
- Terminal panel for ease of connectivity
- Automatic thermal overload protection
- Lubed for life double shielded bearings
- Switchless design for increased reliability

Applications:

- Fans
- Pumps
- Blowers
- Condensers
- Air handling
- HVAC systems
- General purpose applications

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Voltage	Full Load Amps	S.F.	Notes (a)
1/4	1800	48YZ	YPC144A	489	HV1	10.68	18	115	2.5	1	
	1200	48YZ	YPC164A	555	HV1	10.68	22	115	2.8	1	
1/3	1800	48YZ	YPC244A	529	HV1	10.68	21	115	3.4	1	
	1200	56YZ	YPC245A	537	HV1	10.68	21	115	3.4	1	
1/2	1800	48YZ	YPC344A	608	HV1	10.68	22	115	5.1	1	
		56YZ	YPC345A	616	HV1	10.68	24	115	5.1	1	
	1200	48YZ	YPC364A	695	HV1	11.31	27	115	5.4	1	

(a) See notes on inside back flap.

Ventilation fan, three phase TEAO, C-Face, footless

1/2 thru 1 Hp

IP44*



Features:

- Terminal panel for ease of connectivity
- Lubed for life double sealed bearings
- Locked DE bearing to allow mounting in any configuration

Applications:

- Fans
- Pumps
- Blowers
- Condensers
- Air handling
- HVAC systems
- General purpose applications

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
1/2	900	56C	VAOM3560	1,108	HV3	12.68	50	64	208-230/460	1.6	
1	900	56C	VAOM3527	1,314	HV3	14.93	57	74	208-230/460	3.2	

(a) See notes on inside back flap.

*IP54 when Drain Fitting Kit #HA5027A03 is installed in the weep holes (48 thru 256T frame motors only)