

**V\*S Master Vector Duty, three phase, totally enclosed (continued)**

Hp	Base Speed RPM	C.H. Speed RPM	NEMA Frame	Enclosure	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
15	1800	2700	254TC	TEFC	<b>ZDVSM2333T</b>	8,610	VS3	26.83	295	92.4	230/460	18	2, 46, 48
			256TC	TENV	<b>ZDVSNM2333T</b>	9,297	VS4	24.05	348	93.6	230/460	18.5	2, 46, 48
			256TC	TEBC	<b>ZDM2333T</b>	8,091	VS2	33.07	317	92.4	230/460	18.1	2, 8, 46, 70, 106
			256TC	TEBC	<b>ZDM2333T-5</b>	8,091	VS2	34.15	289	92.4	575	14.5	2, 8, 46, 70, 106
			254TC	TENV	<b>ZDNM2333T</b>	9,297	VS4	24.05	286	92.4	230/460	18.5	2, 8, 46, 60, 106
20	1800	2700	284T	TEBC	<b>ZDM4100T</b>	14,414	VS2	36.48	445	93	230/460	19.7	2, 8, 45, 46, 70, 106
			256TC	TEFC	<b>ZDVSM2334T</b>	9,098	VS3	26.83	317	93	230/460	24	2, 46, 48
			256TC	TEBC	<b>ZDM2334T</b>	8,482	VS2	33.07	342	93	230/460	24	2, 8, 46, 70, 106
			256TC	TEBC	<b>ZDM2334T-5</b>	8,482	VS2	34.15	340	93	575	19	2, 8, 46, 70, 106
			284T	TENV	<b>ZDNM2334T</b>	9,390	VS4	27.36	405	94.5	230/460	25.5	2, 8, 45, 46, 60, 106
25	1800	2700	286T	TEBC	<b>ZDM4102T</b>	15,934	VS2	36.48	462	93	230/460	26	2, 8, 45, 46, 70, 106
			284TC	TEFC	<b>ZDVSM4103T</b>	10,794	VS3	30.42	458	93.6	230/460	30	2, 46, 48
			284T	TEBC	<b>ZDM4103T</b>	9,898	VS2	36.48	416	93.6	230/460	30	2, 8, 45, 46, 70, 106
			324T	TEBC	<b>ZDM4111T</b>	17,826	VS2	38.92	615	93	230/460	32	2, 8, 45, 46, 70, 106
			286TC	TEFC	<b>ZDVSM4104T</b>	11,533	VS3	30.42	472	94.1	230/460	36	2, 46, 48
30	1800	2700	286T	TEBC	<b>ZDM4104T</b>	11,009	VS2	36.48	445	93.6	230/460	38	2, 8, 45, 46, 70, 106
			326T	TEBC	<b>ZDM4117T</b>	19,567	VS2	38.92	624	93	230/460	39	2, 8, 45, 46, 70, 106
			324T	TEFC	<b>ZDVSM4110T</b>	12,874	VS3	33.14	716	94.1	230/460	50	2, 46, 48
40	1800	2700	324T	TEBC	<b>ZDM4110T</b>	14,042	VS2	38.92	610	94.5	230/460	47	2, 8, 45, 46, 70, 106
			326T	TEFC	<b>ZDVSM4115T</b>	15,110	VS3	33.14	721	94.5	230/460	60	2, 46, 48
			326T	TEBC	<b>ZDM4115T</b>	15,471	VS2	38.92	631	94.5	230/460	57	2, 8, 45, 46, 70, 106
60	1800	2700	364T	TEFC	<b>ZDVSM4314T</b>	18,047	VS3	33.44	907	94.2	230/460	71.2	2, 46, 48
75	1800	2700	365T	TEFC	<b>ZDVSM4316T</b>	21,895	VS3	33.44	944	94.3	230/460	89.2	2, 46, 48
100	1800	2700	405T	TEFC	<b>ZDVSM4400T-4</b>	27,476	VS3	38.31	1230	94.1	460	115	2, 46, 48
125	1800	2700	444T	TEFC	<b>ZDVSM4410T-4</b>	33,426	VS3	49.07	1667	94.1	460	150	2, 46, 48
150	1800	2700	445T	TEFC	<b>ZDVSM4406T-4</b>	39,349	VS3	49.07	1806	95	460	177	2, 46, 48
200	1800	2700	447T	TEFC	<b>ZDVSM4407T-4</b>	46,106	VS3	52.36	2203	95.4	460	226	2, 46, 48
250	1800	2700	449T	TEFC	<b>ZDVSM4408T-4</b>	64,003	VS3	57.56	2550	95.8	460	277	2, 46, 48
300	1800	2700	449T	TEFC	<b>ZDVSM44304T-4</b>	64,003	VS3	57.56	2817	96.2	460	338	2, 46, 48

(a) See notes on inside back flap.

■ Cast iron frame

Continuous constant torque to zero speed