


Series: LRXA-TPA, BRXA-TPA, LKRXA-TPA, BKRXA-TPA

Stainless steel light duty castors with bolt hole fitting, wheel with thermoplastic rubber tread

50 - 120 kg

RoHS



Brackets: LRXA/BRXA, LKRXA/BKRXA series - Made of pressed high-quality, chromium-nickel stainless steel (Material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the swivel head, strong central kingpin, ball protection by the special top plate and ball disc design. The special Blickle dynamic riveting process of the swivel head results in minimal swivel head play and smooth rolling characteristics with an increased service life achieved by the work hardening of the ball race grooves. All parts incl. axle material are corrosion-resistant.

Wheels: TPA series - Tread: Made of high-quality thermoplastic rubber-elastomer (TPE), containing traces of oil, 85° shore A, grey, non-marking. Wheel centre: Made of high-quality, impact-resistant polypropylene, silver grey (black for electrically conductive '-ELS' version).

Bearing types: Plain bore or a centrally encapsulated, sealed ball bearing (C). Ball bearing (C) with synthetic thread guard and additional ball bearing seals as standard.

Detailed description: Page 88 and 42

Bolted wheel axle. Vibration-ground finished.

Bracket overview: Page 69

Wheel and swivel head 'stop-fix' brake: Page 80



Swivel castors	Fixed castors	Swivel castors with 'stop-fix' brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LRXA-TPA 50G	BRXA-TPA 50G	LRXA-TPA 50G-FI	50	19	50	Plain bore	69	43	11	25
LRXA-TPA 50KD-FK	BRXA-TPA 50KD-FK	LRXA-TPA 50KD-FI-FK	50	19	50	Ball bearing (C)	69	43	11	25
LRXA-TPA 75G	BRXA-TPA 75G	LRXA-TPA 75G-FI	75	25	75	Plain bore	98	43	11	29
LRXA-TPA 75KD-FK	BRXA-TPA 75KD-FK	LRXA-TPA 75KD-FI-FK	75	25	75	Ball bearing (C)	98	43	11	29
LKRXA-TPA 80G	BKRXA-TPA 80G	LKRXA-TPA 80G-FI	80	32	100	Plain bore	108	57	13	40
LKRXA-TPA 80G-11		LKRXA-TPA 80G-11-FI	80	32	100	Plain bore	108	57	11	40
LKRXA-TPA 80KD-FK	BKRXA-TPA 80KD-FK	LKRXA-TPA 80KD-FI-FK	80	32	100	Ball bearing (C)	108	57	13	40
LKRXA-TPA 80KD-11-FK		LKRXA-TPA 80KD-11-FI-FK	80	32	100	Ball bearing (C)	108	57	11	40
LKRXA-TPA 101G	BKRXA-TPA 101G	LKRXA-TPA 101G-FI	100	32	110	Plain bore	133	57	13	40
LKRXA-TPA 101G-11		LKRXA-TPA 101G-11-FI	100	32	110	Plain bore	133	57	11	40
LKRXA-TPA 101KD-FK	BKRXA-TPA 101KD-FK	LKRXA-TPA 101KD-FI-FK	100	32	110	Ball bearing (C)	133	57	13	40
LKRXA-TPA 101KD-11-FK		LKRXA-TPA 101KD-11-FI-FK	100	32	110	Ball bearing (C)	133	57	11	40
LKRXA-TPA 126G	BKRXA-TPA 126G	LKRXA-TPA 126G-FI	125	32	120	Plain bore	158	57	13	40
LKRXA-TPA 126G-11		LKRXA-TPA 126G-11-FI	125	32	120	Plain bore	158	57	11	40
LKRXA-TPA 126KD-FK	BKRXA-TPA 126KD-FK	LKRXA-TPA 126KD-FI-FK	125	32	120	Ball bearing (C)	158	57	13	40
LKRXA-TPA 126KD-11-FK		LKRXA-TPA 126KD-11-FI-FK	125	32	120	Ball bearing (C)	158	57	11	40

18

Options



	Image plain bore version	Electrically conductive version, non-marking grey *	With synthetic expander fitting, corrosion-resistant	With stainless steel plug-in stem **	Bumpers
Technical description page		36, 38	75	74	84
Product code suffix		-ELS	refer to page 352	refer to page 352	AG / ARG series
Available for		all sizes	swivel castors bolt hole Ø11 (except ELS)	swivel castors with wheel Ø 125 mm	refer to page 352

* Load capacity is reduced by 35 %
 ** In acc. to DIN 18867-8 (large-scale catering equipment)