

TLS 2200® General ID Materials

www.BradyID.com/tls2200



TLS 2200® General Identification Materials

Brady's industrial materials are designed and produced to meet the exacting needs and requirements of harsh industrial environments. They are made of durable, heavy-duty material and aggressive adhesive that's proven to stick to almost any industrial environment surface, including machinery, equipment, floors, walls, racks and more.

Brady's industrial materials are made to stick and stay stuck - so you can create facility and safety identification once, knowing it will still be there years down the line.

Printer Compatibility

All general identification materials on the following pages are only compatible with:



TLS 2200® Label Printer

See Page 36



TLS PC Link™ Printer

See Page 37



TLS 2200® General Identification Materials:

B-422 Polyester Material

Color: White Finish: Gloss

White label stock with glossy finish and 2 mils of adhesive for rough surface applications, including low surface energy plastics. Designed to withstand solvent exposure. UL rated for surfaces commonly used in solar panel manufacturing. Also used for component identification, barcoding, and asset and inventory tracking.

Performance Attributes:




Figure 29




Figure 33




Figure 34




Figure 40




Figure 54

Diagram	Part Number	B-#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Row	Labels Per Pkg	Rec. Ribbon
Fig. 34	PTL-39-422	B-422	Polyester	White	0.375 (9.5)	0.600 (15.2)	1	750	R6010
Fig. 33	PTL-46-422	B-422	Polyester	White	0.375 (9.5)	50 ft. (15.2 m)	1	1 Roll Cont.	R6010
Fig. 29	PTL-44-422	B-422	Polyester	White	0.500 (12.7)	0.375 (9.5)	1	500	R6010
Fig. 29	PTL-7-422	B-422	Polyester	White	0.500 (12.7)	0.500 (12.7)	1	500	R6010
Fig. 29	PTL-5-422	B-422	Polyester	White	0.500 (12.7)	0.200 (5.1)	1	750	R6010
Fig. 33	PTL-8-422	B-422	Polyester	White	0.500 (12.7)	50 ft. (15.2 m)	1	1 Roll Cont.	R6010
Fig. 29	PTL-16-422	B-422	Polyester	White	1.000 (25.4)	0.375 (9.5)	1	500	R6010
Fig. 29	PTL-17-422	B-422	Polyester	White	1.000 (25.4)	0.500 (12.7)	1	500	R6010
Fig. 29	BPTL-20-422	B-422	Polyester	White	1.000 (25.4)	2.000 (50.8)	1	1000	R6010
Fig. 29	PTL-19-422	B-422	Polyester	White	1.000 (25.4)	1.000 (25.4)	1	250	R6010
Fig. 33	PTL-42-422	B-422	Polyester	White	1.000 (25.4)	50 ft. (15.2 m)	1	1 Roll Cont.	R6010
Fig. 40	PTPSL-17-422	B-422	Polyester	White	1.000 (25.4)	0.500 (12.7)	1	500	R6010
Fig. 29	PTL-29-422	B-422	Polyester	White	1.050 (38.1)	0.500 (12.7)	1	500	R6010
Fig. 29	PTL-45-422	B-422	Polyester	White	1.050 (38.1)	0.375 (9.5)	1	500	R6010
Fig. 29	PTL-30-422	B-422	Polyester	White	1.500 (38.1)	0.750 (19.1)	1	250	R6010
Fig. 29	PTL-32-422	B-422	Polyester	White	1.500 (38.1)	1.500 (38.1)	1	250	R6010
Fig. 54	PTL-35-422-PROP	B-422	Polyester	Gray	1.630 (41.4)	0.750 (19.1)	1	250	R6010
Fig. 33	PTL-43-422	B-422	Polyester	White	1.900 (48.3)	50 ft. (15.2 m)	1	1 Roll Cont.	R6010
Fig. 29	PTL-20-422	B-422	Polyester	White	2.000 (50.8)	1.000 (25.4)	1	100	R6010
Fig. 40	PTPSL-20-422	B-422	Polyester	White	2.000 (50.8)	1.000 (25.4)	1	100	R6010
Fig. 40	PTPSL-26-422	B-422	Polyester	White	2.750 (69.9)	1.250 (31.8)	1	100	R6010
Fig. 29	PTL-22-422	B-422	Polyester	White	3.000 (76.2)	1.000 (25.4)	1	100	R6010
Fig. 29	PTL-37-422	B-422	Polyester	White	3.000 (76.2)	1.900 (48.3)	1	100	R6010
Fig. 40	PTPSL-50-422	B-422	Polyester	White	3.000 (76.2)	1.650 (41.9)	1	100	R6010
Fig. 29	PTL-23-422	B-422	Polyester	White	4.000 (101.6)	1.000 (25.4)	1	100	R6010
Fig. 29	PTL-38-422	B-422	Polyester	White	4.000 (101.6)	1.900 (48.3)	1	100	R6010