



The IDXPERT™ printer has been discontinued, but Brady continues to manufacture and stock labels and accessories for the printer!

Catalog #	Description
LABXPERT-SER-USB	Serial-to-USB adapter for PC cable
PCK-6	Cleaning Kit

General ID, 5S Lean, Facility and Safety ID (B-422, B-428, B-483, B-499 and B-595)

- B-422 Polyester Material:** Permanent adhesive, good for powder-coated and textured surfaces. Best on flat surfaces. Temp. range: -40°F to 212°F (-40°C to 100°C). UL recognized.
- B-428 Metallized Polyester Material:** Permanent adhesive, silver finish. Temp. range: -40°F to 176°F (-40°C to 80°C). UL recognized.
- B-483 Polyester Material:** Permanent adhesive for powder-coated and textured surfaces. Best on flat surfaces. Temp. range: -40°F to 248°F (-40°C to 120°C). UL recognized.
- B-499 Nylon Cloth Material:** Permanent adhesive. Pliable for rough or smooth surfaces. Temp. range: -94°F to 194°F (-70°C to 90°C). UL recognized.
- B-595 Indoor / Outdoor Vinyl Material:** Permanent adhesive, very pliable, good for rough surfaces and outdoor use. Temp. range: -40°F to 180°F (-40°C to 82°C). UL recognized.




Figure 29



Figure 33




Figure 46
(Includes black border)

Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll
B-422 Polyester Labels							
Fig. 29	X-7-422	B-422	Polyester	Black on White	0.500 (12.7)	0.500 (12.7)	350
Fig. 29	X-19-422	B-422	Polyester	Black on White	1.000 (25.4)	1.000 (25.4)	250
Fig. 29	X-132-422	B-422	Polyester	Black on White	1.500 (38.1)	1.250 (13.8)	250
Fig. 29	X-30-422	B-422	Polyester	Black on White	1.500 (38.1)	0.750 (19.1)	250
B-428 Metallized Polyester Labels							
Fig. 29	X-17-428-SV-BK	B-428	Polyester	Light Gray	1.000 (25.4)	0.500 (12.7)	500
Fig. 46	X-24-428-SVBB-BK	B-428	Polyester	Light Gray	1.130 (28.7)	0.500 (12.7)	500
Fig. 29	X-29-428-SV-BK	B-428	Polyester	Light Gray	1.500 (38.1)	0.500 (12.7)	500
Fig. 29	X-30-428-SV-BK	B-428	Polyester	Light Gray	1.500 (38.1)	0.750 (19.1)	325
Fig. 29	X-20-428-SV-BK	B-428	Polyester	Light Gray	2.000 (50.8)	1.000 (25.4)	100
B-483 Polyester Labels							
Fig. 29	X-17-483	B-483	Polyester	Black on White	1.000 (25.4)	0.500 (12.7)	500
Fig. 29	X-20-483	B-483	Polyester	Black on White	2.000 (50.8)	1.000 (25.4)	100
Fig. 29	X-61-483	B-483	Polyester	Black on White	2.000 (50.8)	0.500 (12.7)	100
B-499 Nylon Cloth Labels							
Fig. 29	X-130-499	B-499	Nylon Cloth	Black on White	0.375 (9.5)	0.750 (19.1)	300
Fig. 33	XC-375-499	B-499	Nylon Cloth	Black on White	0.375 (9.5)	20 ft. (6.1 m)	1 roll (cont.)
Fig. 33	XC-500-499	B-499	Nylon Cloth	Black on White	0.500 (12.7)	20 ft. (6.1 m)	1 roll (cont.)
Fig. 29	X-11-499	B-499	Nylon Cloth	Black on White	0.750 (19.1)	0.500 (12.7)	275
Fig. 33	XC-750-499	B-499	Nylon Cloth	Black on White	0.750 (19.1)	20 ft. (6.1 m)	1 roll (cont.)
Fig. 29	X-84-499	B-499	Nylon Cloth	Black on White	0.900 (22.9)	0.500 (12.7)	250
Fig. 33	XC-1000-499	B-499	Nylon Cloth	Black on White	1.000 (25.4)	20 ft. (6.1 m)	1 roll (cont.)
Fig. 29	X-162-499	B-499	Nylon Cloth	Black on White	1.500 (38.1)	0.500 (12.7)	165

General ID labels continued on next page.