



Table No. 1

Specifications

Sprocket Number	Bush-ing	Bore Range		Type	No. Teeth	Diameters			Dimensions						Wt. Lbs.
		Min.	Max.			P.D.	O.D.	Flange	E	F	H	K	L	M	
FOR 8M20 BELTS — 8mm PITCH — 20mm (.79") WIDE															
B208M20B	—	1/2"	5/8"	6F	20	2.005"	1.951"	2.375"	5/8"	1 1/8"	1 3/8"	—	1 3/4"	0"	.9
B218M20B	—	1/2	3/4	6F	21	2.105	2.051	2.375	5/8	1 1/8	1 1/2	—	1 3/4	0	1.0
B228M20B	—	1/2	7/8	6F	22	2.206	2.152	2.563	5/8	1 1/8	1 5/8	—	1 3/4	0	1.6
B248M20JA	JA	1/2	1 1/4	E1F	24	2.406	2.352	2.75	9/16	1 1/8	—	—	1 1/16	7/16	1.5
B268M20JA	JA	1/2	1 1/4	E1F	26	2.607	2.553	2.938	9/16	1 1/8	—	—	1 1/16	7/16	1.8
B288M20JA	JA	1/2	1 1/4	B1F	28	2.807	2.753	3.156	1/16	1 1/8	—	9/16"	1	1/16	1.5
B288M20H	H	3/8	1 1/2	E1F	28	2.807	2.753	3.156	1/4	1 1/8	—	—	1 1/4	3/8	1.85
B308M20JA	JA	1/2	1 1/4	C1F	30	3.008	2.954	3.344	1/16	1 1/8	—	9/16	1	1/16	2.0
B308M20H	H	3/8	1 1/2	E1F	30	3.008	2.954	3.344	1/4	1 1/8	—	—	1 1/4	3/8	1.9
B328M20JA	JA	1/2	1 1/4	C1F	32	3.208	3.154	3.563	1/4	1 1/8	—	1/4	1	3/8	2.1
B328M20H	H	3/8	1 1/2	C1F	32	3.208	3.154	3.563	1/8	1 1/8	—	1/4	1 1/4	0	2.0
B348M20SH	SH	1/2	1 5/8	D1F	34	3.409	3.355	3.75	3/16	1 1/8	—	5/16	1 1/4	1/16	2.2
B368M20SH	SH	1/2	1 5/8	D1F	36	3.609	3.555	3.938	3/16	1 1/8	—	5/16	1 1/4	1/16	2.5
B388M20SH	SH	1/2	1 5/8	D1F	38	3.810	3.756	4.156	3/16	1 1/8	—	5/16	1 1/4	1/16	2.8
B408M20SH	SH	1/2	1 5/8	D1F	40	4.010	3.956	4.334	3/16	1 1/8	—	5/16	1 1/4	1/16	3.4
B448M20SDS	SDS	1/2	2	C1F	44	4.411	4.357	4.75	3/16	1 1/8	—	3/8	1 5/16	0	3.2
B488M20SDS	SDS	1/2	2	C1F	48	4.812	4.758	5.188	3/16	1 1/8	—	3/8	1 5/16	0	3.4
B568M20SDS	SDS	1/2	2	C1F	56	5.614	5.560	5.938	3/16	1 1/8	—	3/8	1 5/16	0	4.5
B648M20SDS	SDS	1/2	2	C1F	64	6.416	6.362	6.75	3/16	1 1/8	—	3/8	1 5/16	0	6.2
B728M20SDS	SDS	1/2	2	C1F	72	7.218	7.164	7.563	3/16	1 1/8	—	3/8	1 5/16	0	6
B808M20SDS	SDS	1/2	2	C2F	80	8.020	7.966	8.375	3/16	1 1/8	—	3/8	1 5/16	0	6.5
B808M20SK	SK	1/2	2 5/8	C2F	80	8.020	7.966	8.375	25/32	1 1/8	—	1/16*	1 5/16	3/32	11.6
B908M20SDS	SDS	1/2	2	D2	90	9.023	8.969	—	3/16	1 1/8	—	3/8	1 5/16	0	7
B908M20SK	SK	1/2	2 5/8	C3	90	9.023	8.969	—	25/32	1 1/8	—	1/16*	1 5/16	3/32	11.8
B1128M20SK	SK	1/2	2 5/8	C3	112	11.229	11.175	—	3/4	1 1/8	—	1/16	1 5/16	1/16	10.5
B1448M20SF	SF	1/2	2 15/16	C3	114	14.447	14.383	—	3/4	1 1/8	—	1/16	2 1/16	1/16	14.5

NOTE—Numerals in Type Designations mean: 1=Solid, 2=Web, 3=Arm Construction; F=Flanged Sprocket.

* Hub Projection