

Table No.1

Stock Single and Multiple Strand Chain and Parts

Part Number	CHAIN			PARTS ●		
	Pitch	Feet per Package ▲	Wt-Lbs. per Package	Spring Clip Connecting Links	Cotter Pin Connecting Links	Offset Links
SINGLE STRAND ROLLER CHAIN						
J35 RIV 10 FT CH	3/8"	10(2)	2.3	J35 S/C C/L (25)	—	J35 O/S C/L (25)
J35 RIV 250 FT CH	3/8	250(50)	57.5	J35 S/C C/L (25)	—	J35 O/S C/L (25)
J41 RIV 10 FT CH	1/2	10(2)	2.8	J41 S/C C/L (25)	—	J41 O/S C/L (25)
J41 RIV 250 FT CH	1/2	250(50)	70.0	J41 S/C C/L (25)	—	J41 O/S C/L (26)
J40 RIV 10 FT CH	1/2	10(2)	4.1	J40 S/C C/L (25)	—	J40 O/S C/L (25)
J40 RIV 200 FT CH	1/2	200(40)	82.0	J40 S/C C/L (25)	—	J40 O/S C/L (25)
J50 RIV 10 FT CH	5/8	10(2)	6.9	J50 S/C C/L (25)	—	J50 O/S C/L (25)
J50 RIV 100 FT CH	5/8	100(20)	69.0	J50 S/C C/L (25)	—	J50 O/S C/L (25)
J60 RIV 10 FT CH	3/4	10(2)	10.4	J60 S/C C/L (25)	J60 C/P C/L (25)	J60 O/S C/L (25)
J60 RIV 100 FT CH	3/4	100(20)	104.0	J60 S/C C/L (25)	J60 C/P C/L (25)	J60 O/S C/L (25)
J80 RIV 10 FT CH	1	10(1)	17.7	—	J80 C/P C/L (10)	J80 O/S C/L (10)
J80 RIV 50 FT CH	1	50(5)	88.5	—	J80 C/P C/L (10)	J80 O/S C/L (10)
J80 CP 10 FT CH	1	10(1)	17.7	—	J80 C/P C/L (10)	J80 O/S C/L (10)
J100 RIV 10 FT CH	1 1/4	10(1)	25.9	—	J100 C/P C/L (10)	J100 O/S C/L (10)
J100 RIV 50 FT CH	1 1/4	50(5)	129.5	—	J100 C/P C/L (10)	J100 O/S C/L (10)
J100 CP 10 FT CH	1 1/4	10(1)	25.9	—	J100 C/P C/L (10)	J100 O/S C/L (10)
J120 RIV 10 FT CH	1 1/2	10(1)	40.5	—	J120 C/P C/L (5)	J120 O/S C/L (5)
J120 RIV 50 FT CH	1 1/2	50(5)	202.5	—	J120 C/P C/L (5)	J120 O/S C/L (5)
J120 CP 10 FT CH	1 1/2	10(1)	40.5	—	J120 C/P C/L (5)	J120 O/S C/L (5)
J140 RIV 10/2 FT CH	1 3/4	10.2(1)	52.1	—	J140 C/P C/L (5)	J140 O/S C/L (5)
J140 CP 10/2 FT CH	1 3/4	10.2(1)	52.1	—	J140 C/P C/L (5)	J140 O/S C/L (5)
J160 RIV 10 FT CH	2	10(1)	68.5	—	J160 C/P C/L (2)	J160 O/S C/L (2)
J160 CP 10 FT CH	2	10(1)	68.5	—	J160 C/P C/L (2)	J160 O/S C/L (2)
DOUBLE STRAND ROLLER CHAIN						
J35-2 RIV 10 FT CH	3/8	10(2)	4.6	J35-2 S/C C/L (25)	—	J35-2 O/S C/L (25)
J40-2 RIV 10 FT CH	1/2	10(2)	8.2	J40-2 S/C C/L (25)	—	J40-2 O/S C/L (25)
J50-2 RIV 10 FT CH	5/8	10(2)	13.8	J50-2 S/C C/L (25)	—	J50-2 O/S C/L (25)
J60-2 RIV 10 FT CH	3/4	10(2)	20.8	J60-2 S/C C/L (25)	J60-2 C/P C/L (25)	J60-2 O/S C/L (25)
J60-2 CP 10 FT CH	3/4	10(2)	20.8	J60-2 S/C C/L (25)	J60-2 C/P C/L (25)	J60-2 O/S C/L (25)
J80-2 RIV 10 FT CH	1	10(1)	35.4	—	J80-2 C/P C/L (10)	J80-2 O/S C/L (10)
J80-2 CP 10 FT CH	1	10(1)	35.4	—	J80-2 C/P C/L (10)	J80-2 O/S C/L (10)
J100-2 RIV 10 FT CH	1 1/4	10(1)	51.8	—	J100-2 C/P C/L (5)	J100-2 O/S C/L (5)
J100-2 CP 10 FT CH	1 1/4	10(1)	51.8	—	J100-2 C/P C/L (5)	J100-2 O/S C/L (5)
J120-2 RIV 10 FT CH	1 1/2	10(1)	81.0	—	J120-2 C/P C/L (2)	J120-2 O/S C/L (2)
J120-2 CP 10 FT CH	1 1/2	10(1)	81.0	—	J120-2 C/P C/L (2)	J120-2 O/S C/L (2)
J140-2 CP 10/2 FT CH	1 3/4	10.2(1)	104.1	—	J140-2 C/P C/L (2)	J140-2 O/S C/L (2)
J160-2 CP 10 FT CH	2	10(1)	137.0	—	J160-2 C/P C/L (1)	J160-2 O/S C/L (1)
TRIPLE STRAND ROLLER CHAIN						
J35-3 RIV 10 FT CH	3/8	10(2)	6.9	J35-3 S/C C/L (25)	—	J35-3 O/S C/L (25)
J40-3 RIV 10 FT CH	1/2	10(2)	12.3	J40-3 S/C C/L (25)	—	J40-3 O/S C/L (25)
J50-3 RIV 10 FT CH	5/8	10(2)	20.7	J50-3 S/C C/L (25)	—	J50-3 O/S C/L (25)
J60-3 RIV 10 FT CH	3/4	10(2)	31.2	J60-3 S/C C/L (25)	J60-3 C/P C/L (15)	J60-3 O/S C/L (15)
J60-3 CP 10 FT CH	3/4	10(2)	31.2	J60-3 S/C C/L (25)	J60-3 C/P C/L (15)	J60-3 O/S C/L (15)
J80-3 RIV 10 FT CH	1	10(1)	53.1	—	J80-3 C/P C/L (10)	J80-3 O/S C/L (5)
J80-3 CP 10 FT CH	1	10(1)	53.1	—	J80-3 C/P C/L (10)	J80-3 O/S C/L (5)
				—		
				—		
				—		
				—		

▲ Number of Connecting Links in a Standard Package of Chain is shown in parenthesis.

● Number of Parts per Standard Package shown in Parenthesis.

1. Prestressed to firmly seat chain parts, evenly distribute the working load, establish accurate length and reduce elongation during initial break-in.
2. Meets or exceeds A.N.S.I. horsepower rating requirements. Ratings shown on Pages G58 to G62 apply.