

Eaton 170M1369

Catalog Number: 170M1369

Eaton Bussmann series high speed square body fuse, 700V (UL), 690 V (IEC), 160A, 200 kAIC, Top fuse status indicator, Fuse, Blade end X blade end, Class aR, DIN 43 620

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M1369
	EAN
	5027590440868
UPC	Product Length/Depth
051712216708	105 mm
Product Height	Product Width
46 mm	300 mm
Product Weight	Compliances
135.9 g	CE Marked
	RoHS Compliant
Certifications	
IEC Rated	
UL Recognized	

Product specifications

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

160 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

000

Rated voltage AC

690 V

Center-to-center distance of connections

76.7 mm

Current type

AC

Mounting dimension

M8

Class

Class aR

Clearing (I²T)

16000 at 660 V

Watt losses

32 W

Fuse shape

Square body, slotted offset bolted tags

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

Declarations of conformity

[UKCA 170M size 000 10A to 315A](#)

[CE 170M size 000 10A to 315A](#)

Pre arc (I2T)

2300

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

000

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

/80 Visual indicator

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)