

## STAINLESS STEEL FLEXIBLE CONDUIT (Type 316SS)


| Coated Flex Conduit 25' Length |             | NEMA4X Suitable for damp locations |        |      |                   |             |
|--------------------------------|-------------|------------------------------------|--------|------|-------------------|-------------|
| Trade Size                     | Metric Size | Diameters                          |        | Bend | Wt. 25 Coil (lbs) | Part Number |
|                                |             | OD                                 | ID     |      |                   |             |
| ½"                             | 16          | 0.840"                             | 0.610" | 4 ½" | 5.50"             | S60500CTFC  |
| ¾"                             | 21          | 1.050"                             | 0.790" | 6"   | 7.00"             | S60700CTFC  |
| 1"                             | 27          | 1.315"                             | 1.010" | 10"  | 9.00"             | S61000CTFC  |
| 1 ¼"                           | 35          | 1.660"                             | 1.330" | 11"  | 11.00"            | S61200CTFC  |
| 1 ½"                           | 41          | 1.900"                             | 1.520" | 12"  | 12.00"            | S61500CTFC  |
| 2"                             | 53          | 2.370"                             | 2.060" | 14"  | 20.00"            | S62000CTFC  |



| Clear Coated Flex Conduit 25' Length |             | NEMA4X Suitable for damp locations |        |      |                   |             |
|--------------------------------------|-------------|------------------------------------|--------|------|-------------------|-------------|
| Trade Size                           | Metric Size | Diameters                          |        | Bend | Wt. 25 Coil (lbs) | Part Number |
|                                      |             | OD                                 | ID     |      |                   |             |
| ½"                                   | 16          | 0.840"                             | 0.610" | 4 ½" | 5.50"             | S60500CTCC  |
| ¾"                                   | 21          | 1.050"                             | 0.790" | 6"   | 7.00"             | S60700CTCC  |
| 1"                                   | 27          | 1.315"                             | 1.010" | 10"  | 9.00"             | S61000CTCC  |
| 1 ¼"                                 | 35          | 1.660"                             | 1.330" | 11"  | 11.00"            | S61200CTCC  |
| 1 ½"                                 | 41          | 1.900"                             | 1.520" | 12"  | 12.00"            | S61500CTCC  |
| 2"                                   | 53          | 2.370"                             | 2.060" | 14"  | 20.00"            | S62000CTCC  |




| Bare Flex Conduit 25' Length |             | NEMA4X Suitable for damp locations |        |      |                   |             |
|------------------------------|-------------|------------------------------------|--------|------|-------------------|-------------|
| Trade Size                   | Metric Size | Diameters                          |        | Bend | Wt. 25 Coil (lbs) | Part Number |
|                              |             | OD                                 | ID     |      |                   |             |
| ½"                           | 16          | 0.744"                             | 0.610" | 4"   | 4.50"             | S60500CTFX  |
| ¾"                           | 21          | 0.960"                             | 0.790" | 4 ½" | 5.50"             | S60700CTFX  |
| 1"                           | 27          | 1.160"                             | 1.010" | 6"   | 7.00"             | S61000CTFX  |
| 1 ¼"                         | 35          | 1.500"                             | 1.330" | 7 ½" | 8.50"             | S61200CTFX  |
| 1 ½"                         | 41          | 1.750"                             | 1.520" | 9"   | 10.00"            | S61500CTFX  |
| 2"                           | 53          | 2.125"                             | 2.020" | 10"  | 13.00"            | S62000CTFX  |




## STAINLESS STEEL FLEXIBLE CONNECTORS (Type 316SS)

| Flex Connector Male 90 Elbow |             |           | NEMA4X Suitable for damp locations |        |        |             |
|------------------------------|-------------|-----------|------------------------------------|--------|--------|-------------|
| Trade Size                   | Metric Size | Wt. (lbs) | A                                  | B      | C      | Part Number |
| ½"                           | 16          | 0.27      | 1.950"                             | 1.250" | 2.150" | S60500FC90  |
| ¾"                           | 21          | 0.50      | 2.250"                             | 1.540" | 2.630" | S60700FC90  |
| 1"                           | 27          | 0.72      | 2.800"                             | 1.860" | 3.000" | S61000FC90  |
| 1 ¼"                         | 35          | 0.95      | 3.150"                             | 2.250" | 3.150" | S61200FC90  |
| 1 ½"                         | 41          | 1.55      | 3.750"                             | 2.580" | 3.750" | S61500FC90  |
| 2"                           | 53          | 2.35      | 4.450"                             | 3.050" | 4.750" | S62000FC90  |



| Flex Connector Male Straight |             |           | NEMA4X Suitable for damp locations |        |             |
|------------------------------|-------------|-----------|------------------------------------|--------|-------------|
| Trade Size                   | Metric Size | Wt. (lbs) | A                                  | B      | Part Number |
| ½"                           | 16          | 0.17      | 1.950"                             | 1.250" | S60500FCS0  |
| ¾"                           | 21          | 0.24      | 2.250"                             | 1.540" | S60700FCS0  |
| 1"                           | 27          | 0.33      | 2.800"                             | 1.650" | S61000FCS0  |
| 1 ¼"                         | 35          | 0.58      | 3.150"                             | 2.250" | S61200FCS0  |
| 1 ½"                         | 41          | 0.85      | 3.750"                             | 2.650" | S61500FCS0  |
| 2"                           | 53          | 1.19      | 4.450"                             | 3.210" | S62000FCS0  |



• 45° Flex Connectors available in ½", ¾" and 1"