

# Gantry Cranes



## Model K90-2 - 2 Ton Capacity

**QUICKSHIP PROGRAM**

SPECIFICATIONS		Nominal Span (ft.)						
		Clamp Connection				Bolt Connection		
2 Ton Capacity*		10	12	14	16	20	24	
Maximum Height Under Beam (ft.)	7	Model Number	K90-2-7/10	K90-2-7/12	K90-2-7/14	K90-2-7/16	K90-2-7/20	K90-2-7/24
		Inside Span (A)	10'-5"	12'-5"	14'-5"	16'-5"	19'-7"	23'-7"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
		Weight (lbs.)	675	700	850	900	1400	1600
		Minimum Height	5'-2"				5'-3"	
		Support Width (C)	4'-0"					
	9	Model Number	K90-2-9/10	K90-2-9/12	K90-2-9/14	K90-2-9/16	K90-2-9/20	K90-2-9/24
		Inside Span (A)	10'-5"	12'-5"	14'-5"	16'-5"	19'-7"	23'-7"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
		Weight (lbs.)	750	800	925	975	1475	1675
		Minimum Height	6'-2"				6'-3"	
		Support Width (C)	5'-0"					
	10	Model Number	K90-2-10/10	K90-2-10/12	K90-2-10/14	K90-2-10/16	K90-2-10/20	K90-2-10/24
		Inside Span (A)	10'-5"	12'-5"	14'-5"	16'-5"	19'-7"	23'-7"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
		Weight (lbs.)	775	825	975	1025	1500	1700
		Minimum Height	7'-2"				7'-3"	
		Support Width (C)	5'-6"					
	12	Model Number	K90-2-12/10	K90-2-12/12	K90-2-12/14	K90-2-12/16	K90-2-12/20	K90-2-12/24
		Inside Span (A)	10'-5"	12'-5"	14'-5"	16'-5"	19'-7"	23'-7"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
		Weight (lbs.)	875	900	1050	1100	1600	1800
		Minimum Height	8'-2"				8'-3"	
		Support Width (C)	6'-6"					
14	Model Number	K90-2-14/10	K90-2-14/12	K90-2-14/14	K90-2-14/16	K90-2-14/20	K90-2-14/24	
	Inside Span (A)	10'-5"	12'-5"	14'-5"	16'-5"	19'-7"	23'-7"	
	Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"	
	Weight (lbs.)	950	975	1125	1175	1650	1875	
	Minimum Height	9'-2"				9'-3"		
	Support Width (C)	7'-6"						
16	Model Number	K90-2-16/10	K90-2-16/12	K90-2-16/14	K90-2-16/16	K90-2-16/20	K90-2-16/24	
	Inside Span (A)	10'-5"	12'-5"	14'-5"	16'-5"	19'-7"	23'-7"	
	Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-2"	
	Weight (lbs.)	1000	1025	1175	1225	1700	1925	
	Minimum Height	10'-2"				10'-3"		
	Support Width (C)	7'-6"						
Beam Height (in.)		8		10		12		15
Flange Width (in.)		4		4.7		5		5.5
Caster Diameter (in.)		8						

\* Total weight of hoist and trolley not to exceed 20% of rated capacity.