

Gantry Cranes

Model K90-3 - 3 Ton Capacity

**QUICKSHIP
PROGRAM**

SPECIFICATIONS		Nominal Span (ft.)						
		Clamp Connection				Bolt Connection		
3 Ton Capacity*		10	12	14	16	20	24	
Maximum Height Under Beam (ft.)	7	Model Number	K90-3-7/10	K90-3-7/12	K90-3-7/14	K90-3-7/16	K90-3-7/20	K90-3-7/24
		Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
		Weight (lbs.)	1000	1050	1100	1250	1675	2125
		Minimum Height	5'-0"					
		Support Width (C)	4'-0"					
	9	Model Number	K90-3-9/10	K90-3-9/12	K90-3-9/14	K90-3-9/16	K90-3-9/20	K90-3-9/24
		Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
		Weight (lbs.)	1100	1175	1225	1375	1750	2250
		Minimum Height	6'-0"					
		Support Width (C)	5'-0"					
	10	Model Number	K90-3-10/10	K90-3-10/12	K90-3-10/14	K90-3-10/16	K90-3-10/20	K90-3-10/24
		Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
		Weight (lbs.)	1175	1200	1275	1425	1800	2300
		Minimum Height	7'-0"					
		Support Width (C)	5'-6"					
12	Model Number	K90-3-12/10	K90-3-12/12	K90-3-12/14	K90-3-12/16	K90-3-12/20	K90-3-12/24	
	Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"	
	Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"	
	Weight (lbs.)	1300	1375	1400	1575	1975	2450	
	Minimum Height	8'-0"						
	Support Width (C)	6'-6"						
14	Model Number	K90-3-14/10	K90-3-14/12	K90-3-14/14	K90-3-14/16	K90-3-14/20	K90-3-14/24	
	Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"	
	Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"	
	Weight (lbs.)	1400	1475	1525	1675	2075	2550	
	Minimum Height	9'-0"						
	Support Width (C)	7'-6"						
16	Model Number	K90-3-16/10	K90-3-16/12	K90-3-16/14	K90-3-16/16	K90-3-16/20	K90-3-16/24	
	Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"	
	Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"	
	Weight (lbs.)	1500	1550	1600	1750	2150	2625	
	Minimum Height	10'-0"						
	Support Width (C)	7'-6"						
Beam Height (in.)		10			12	15	18	
Flange Width (in.)		4.7			5	5.5	6	
Caster Diameter (in.)		8						

* Total weight of hoist and trolley not to exceed 20% of rated capacity.