

Gantry Cranes

Model K90-5 - 5 Ton Capacity

**QUICKSHIP
PROGRAM**

SPECIFICATIONS		Nominal Span (ft.)						
		Clamp Connection				Bolt Connection		
		10	12	14	16	20	24	
Maximum Height Under Beam (ft.)	5 Ton Capacity*							
	7	Model Number	K90-5-7/10	K90-5-7/12	K90-5-7/14	K90-5-7/16	K90-5-7/20	K90-5-7/24
		Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
		Weight (lbs.)	1175	1225	1475	1550	1700	2175
		Minimum Height	5'-1"			5'-2"		
		Support Width (C)	4'-0"					
	9	Model Number	K90-5-9/10	K90-5-9/12	K90-5-9/14	K90-5-9/16	K90-5-9/20	K90-5-9/24
		Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
		Weight (lbs.)	1325	1375	1625	1700	1850	2300
		Minimum Height	6'-1"			6'-2"		
		Support Width (C)	5'-0"					
	10	Model Number	K90-5-10/10	K90-5-10/12	K90-5-10/14	K90-5-10/16	K90-5-10/20	K90-5-10/24
		Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
		Weight (lbs.)	1375	1425	1675	1750	1900	2375
		Minimum Height	7'-1"			7'-2"		
		Support Width (C)	5'-6"					
	12	Model Number	K90-5-12/10	K90-5-12/12	K90-5-12/14	K90-5-12/16	K90-5-12/20	K90-5-12/24
		Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
		Weight (lbs.)	1550	1600	1825	1925	2075	2525
		Minimum Height	8'-1"			8'-2"		
		Support Width (C)	6'-6"					
	14	Model Number	K90-5-14/10	K90-5-14/12	K90-5-14/14	K90-5-14/16	K90-5-14/20	K90-5-14/24
		Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"
		Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"
Weight (lbs.)		1650	1725	1950	2050	2175	2650	
Minimum Height		9'-1"			9'-2"			
Support Width (C)		7'-6"						
16	Model Number	K90-5-16/10	K90-5-16/12	K90-5-16/14	K90-5-16/16	K90-5-16/20	K90-5-16/24	
	Inside Span (A)	9'-5"	11'-5"	13'-5"	15'-5"	19'-5"	23'-5"	
	Overall Length (B)	11'-6"	13'-6"	15'-6"	17'-6"	21'-3"	25'-3"	
	Weight (lbs.)	1725	1800	2025	2125	2275	2725	
	Minimum Height	10'-1"			10'-2"			
	Support Width (C)	7'-6"						
Beam Height (in.)		12	12	15	15	15	18	
Flange Width (in.)		5	5	5.5	5.5	5.5	6	
Caster Diameter (in.)		8						

* Total weight of hoist and trolley not to exceed 20% of rated capacity.



The Caldwell Group • 800-628-4263 • www.caldwellinc.com

Krane-King® Section
2014-2016 Master Catalog