


Gooseneck Spouts


- Swing Spouts – 360° rotation
- Restricted Swing Spouts* – Adjustable rotation of 70° or 120°
- Rigid/Swing Spouts – Adjustable for 360° rotation or fixed position



Model	A	B	C	Outlet Thread
Swing				
GN10ASWGJKABCP	7"	10"	13-1/2"	13/16" - 24 UNS Male
GN10BSWGJKABCP	6-7/8"	10"	13-1/2"	3/8" - 18 NPSM Female
GN12ASWGJKABCP	7"	12"	14-1/2"	13/16" - 24 UNS Male
GN12BSWGJKABCP	6-7/8"	12"	14-1/2"	3/8" - 18 NPSM Female
GN12SWGJKABCP	7"	12"	14-1/2"	Plain
Swing with Atmospheric Vacuum Breaker				
GN12BVBSWGJKABCP	6-3/4"	12"	10-3/4"	3/8" - 18 NPSM Female
Restricted Swing				
GN2ARSJKABCP	6-1/8"	5-1/4"	9-3/4"	13/16" - 24 UNS Male
GN8ARSJKABCP	6"	8"	11-1/4"	13/16" - 24 UNS Male
Rigid/Swing				
GN1AJKABCP	5-7/8"	3-1/2"	8-3/8"	13/16" - 24 UNS Male
GN1BJKABCP	5-1/2"	3-1/2"	8-3/8"	3/8" - 18 NPSM Female
GN1JKABCP	5-7/8"	3-1/2"	8-3/8"	Plain
GN2AH13JKABCP	9-3/8"	5-1/4"	13"	13/16" - 24 UNS Male
GN2AH17JKABCP	13-3/8"	5-1/4"	17"	13/16" - 24 UNS Male
GN2AH8JKABCP	4-3/8"	5-1/4"	8"	13/16" - 24 UNS Male
GN2AJKABCP	6-1/8"	5-1/4"	9-3/4"	13/16" - 24 UNS Male
GN2BH13JKABCP	9"	5-1/4"	13"	3/8" - 18 NPSM Female
GN2BH17JKABCP	12-3/4"	5-1/4"	17"	3/8" - 18 NPSM Female
GN2BH8JKABCP	4"	5-1/4"	8"	3/8" - 18 NPSM Female
GN2BJKABCP	5-5/8"	5-1/4"	9-3/4"	3/8" - 18 NPSM Female
GN2BJKCTF ¹	5-5/8"	5-1/4"	9-3/4"	3/8" - 18 NPSM Female
GN2BJSAM ²	5-5/8"	5-1/4"	9-3/4"	3/8" - 18 NPSM Female
GN2H13JKABCP	9-3/8"	5-1/4"	13"	Plain
GN2H17JKABCP	13-3/8"	5-1/4"	17"	Plain
GN2H8JKABCP	4-3/8"	5-1/4"	8"	Plain
GN2JKABCP	5-5/8"	5-1/4"	9-3/4"	Plain
GN8AJKABCP	6"	8"	11-1/4"	13/16" - 24 UNS Male
GN8BJKABCP	5-3/4"	8"	11-1/4"	3/8" - 18 NPSM Female
GN8BJKCTF ¹	5-3/4"	8"	11-1/4"	3/8" - 18 NPSM Female
GN8JKABCP	6-1/8"	8"	11-1/4"	Plain

¹Tin lined ²Satin antimicrobial finish
 * Available on 201 Series fittings

Model	A	B	C	Outlet Thread
Rigid/Swing with 0.5 GPM Laminar Flow Control Insert				
GN1FC3JKABCP	5-7/8"	3-1/2"	8-3/8"	Plain
GN8AFC3JKABCP	6"	8"	11-1/4"	13/16" - 24 UNS Male
Rigid/Swing with 1.0 GPM Laminar Flow Control Insert				
GN1FC1JKABCP	5-7/8"	3-1/2"	8-3/8"	Plain
GN2FC1JKABCP	6-1/8"	5-1/4"	9-3/4"	Plain
GN2H8FC1JKABCP	4-3/8"	5-1/4"	8"	Plain
GN8BFC1JKABCP	5-3/4"	8"	11-1/4"	3/8" - 18 NPSM Female
GN8FC1JKABCP	6-1/8"	8"	11-1/4"	Plain
Rigid/Swing with 1.5 GPM Laminar Flow Control Insert				
GN1AFCJKABCP	5-7/8"	3-1/2"	8-3/8"	13/16" - 24 UNS Male
GN1FCJKABCP	5-7/8"	3-1/2"	8-3/8"	Plain
GN1BFCJKABCP	5-1/2"	3-1/2"	8-3/8"	3/8" - 18 NPSM Female
GN2AFCJKABCP	6-1/8"	5-1/4"	9-3/4"	13/16" - 24 UNS Male
GN2AH8FCJKABCP	4-3/8"	5-1/4"	8"	13/16" - 24 UNS Male
GN2BFCJKABCP	5-5/8"	5-1/4"	9-3/4"	3/8" - 18 NPSM Female
GN2FCJKABCP	6-1/8"	5-1/4"	9-3/4"	Plain
GN2H8FCJKABCP	4-3/8"	5-1/4"	8"	Plain
GN2H13FCJKABCP	9-3/8"	5-1/4"	13"	Plain
GN8AFCE3JKABCP	6"	8"	11-1/4"	13/16" - 24 UNS Male
GN8AFCJKABCP	6"	8"	11-1/4"	13/16" - 24 UNS Male
GN8BFCJKABCP	5-3/4"	8"	11-1/4"	3/8" - 18 NPSM Female
GN8FCJKABCP	6-1/8"	8"	11-1/4"	Plain
Rigid/Swing with 2.0 GPM Laminar Flow Control Insert				
GN1FC2JKABCP	5-7/8"	3-1/2"	8-3/8"	Plain
GN2FC2JKABCP	6-1/8"	5-1/4"	9-3/4"	Plain
GN8FC2JKABCP	6-1/8"	8"	11-1/4"	Plain
Rigid/Swing with Atmospheric Vacuum Breaker				
GN1BVBVKABCP	5-3/4"	4 1/2"	9-1/2"	3/8" - 18 NPSM Female
GN1BVBFCJKCP	5-3/4"	4-1/2"	9-1/2"	3/8" - 18 NPSM Female
GN2BVBFCJKABCP	5-3/4"	6"	9-1/2"	3/8" - 18 NPSM Female
GN2BVBVKABCP	5-3/4"	6"	9-1/2"	3/8" - 18 NPSM Female
GN8BVBFCJKCP	5-3/4"	8"	9-1/2"	3/8" - 18 NPSM Female
GN8BVBVKABCP	5-3/4"	8"	9-1/2"	3/8" - 18 NPSM Female



High Arch Spouts

- Rigid/Swing Spouts – Field adjustable for 360° rotation or fixed position
- Restricted Swing Spouts* – Field adjustable rotation of 70° or 120°

Model	A	B	C	Outlet Thread
Rigid/Swing				
HA8AJKABCP	8-3/8"	8"	10"	13/16" - 24 UNS Male

Model	A	B	C	Outlet Thread
Restricted Swing				
HA8ARSJKABCP	8-3/8"	8"	10"	13/16" - 24 UNS Male

S-Type Spouts

- Swing Spouts – 360° rotation

Model	A	B	C	Outlet Thread
Swing				
S6LEQJAB	1"	6"	1-5/8"	13/16" - 24 UNS Male

