



SUFFIX OPTION	DESCRIPTION
P	ABS Housing
SS	Satin Finish Stainless housing
SSP	Polished Stainless Housing
AP-13	T&P Valve Assembly
NPT08	1/2" Male NPT Connection
NPT12	3/4" Male NPT Connection - ABS only
2095-1	Disconnect Switch (Nema 4x Rated)

FEATURES AND BENEFITS

- 0.35 gallon (1.3 liter) per minute low activation
- 0.65 gallon (2.5 liter) per minute standard activation
- Unlimited hot water
- Compact 6-1/4 height x 9-5/8 x 2-3/4" (159 x 244 x 70 mm) size
- Meets ADA requirements

INSTANT FLOW® - SR SERIES										
LOW FLOW						°F TEMPERATURE RISE @				
MODEL	ACTIVATION GPM	VOLTS	KW	AMPS	90°C WIRE	0.35 GPM	0.5 GPM	1.0 GPM	1.5 GPM	2.0 GPM
SR-15L/120	0.35	120	1.80	15	14 AWG	35	25	12	8	6
SR-20L/120	0.35	120	2.40	20	12 AWG	47	31	16	11	8
SR-30L/120	0.35	120	3.60	30	10 AWG	70	49	25	16	12
SR-20L/208	0.35	208	4.16	20	12 AWG	81	57	28	19	14
SR-20L/240	0.35	240	4.80	20	12 AWG	90+	66	33	22	16
SR-15L/277	0.35	277	4.15	15	14 AWG	81	57	28	19	14
SR-20L/277	0.35	277	5.54	20	12 AWG	90+	76	38	25	19

INSTANT FLOW® - SR SERIES										
STANDARD FLOW						°F TEMPERATURE RISE @				
MODEL	ACTIVATION GPM	VOLTS	KW	AMPS	90°C WIRE	0.65 GPM	1.0 GPM	1.5 GPM	2.0 GPM	
SR-30/208	0.65	208	6.24	30	10 AWG	66	41	28	21	
SR-40/208	0.65	208	8.32	40	8 AWG	87	57	38	28	
SR-30/240	0.65	240	7.20	30	10 AWG	76	49	33	25	
SR-40/240	0.65	240	9.60	40	8 AWG	90+	66	44	33	
SR-30/277	0.65	277	8.31	30	10 AWG	87	57	38	28	

Note : Local plumbing and electrical codes must be followed for this installation of the water heater and accessories.

