

One-Piece Clamping Collars Recessed Screw - H1C-Series



- Recessed screw head provides an outside surface free of major projections for safety
- Design fully engages the shaft without marring
- Greater axial holding power than set screw collars
- Effective on hard and soft shafts

Black Oxide Steel	Stainless Steel	Aluminum	Bore Size	OD	Width	Clamp Screw	Box Qty	Approx. Weight (oz.)
H1C-012	H1C-012-S	H1C-012-A	1/8	13/16	1/4	4-40 x 3/8	20	0.51
H1C-018	H1C-018-S	H1C-018-A	3/16	13/16	1/4	4-40 x 3/8	20	0.50
H1C-025	H1C-025-S	H1C-025-A	1/4	13/16	1/4	4-40 x 3/8	20	0.45
H1C-031	H1C-031-S	H1C-031-A	5/16	13/16	1/4	4-40 x 3/8	20	0.43
H1C-037	H1C-037-S	H1C-037-A	3/8	1 1/16	5/16	6-32 x 3/8	20	0.95
H1C-043	H1C-043-S	H1C-043-A	7/16	1 1/16	5/16	6-32 x 3/8	20	0.92
H1C-050	H1C-050-S	H1C-050-A	1/2	1 1/4	3/8	8-32 x 1/2	20	1.50
H1C-056	H1C-056-S	H1C-056-A	9/16	1 1/4	3/8	8-32 x 1/2	20	1.50
H1C-062	H1C-062-S	H1C-062-A	5/8	1 1/2	13/32	10-32 x 1/2	20	2.40
H1C-068	H1C-068-S	H1C-068-A	11/16	1 1/2	13/32	10-32 x 1/2	20	2.30
H1C-075	H1C-075-S	H1C-075-A	3/4	1 3/4	1/2	1/4-28 x 5/8	20	3.90
H1C-081	H1C-081-S	H1C-081-A	13/16	1 3/4	1/2	1/4-28 x 5/8	20	3.80
H1C-087	H1C-087-S	H1C-087-A	7/8	1 7/8	1/2	1/4-28 x 5/8	20	4.50
H1C-093	H1C-093-S	H1C-093-A	15/16	1 7/8	1/2	1/4-28 x 5/8	20	4.20
H1C-100	H1C-100-S	H1C-100-A	1	2	1/2	1/4-28 x 5/8	20	4.80
H1C-106	H1C-106-S	H1C-106-A	1 1/16	2	1/2	1/4-28 x 5/8	10	4.60
H1C-112	H1C-112-S	H1C-112-A	1 1/8	2 1/8	1/2	1/4-28 x 3/4	10	5.30
H1C-118	H1C-118-S	H1C-118-A	1 3/16	2 1/8	1/2	1/4-28 x 3/4	10	5.00
H1C-125	H1C-125-S	H1C-125-A	1 1/4	2 1/4	1/2	1/4-28 x 3/4	10	5.70
H1C-131	H1C-131-S	H1C-131-A	1 5/16	2 1/4	1/2	1/4-28 x 3/4	10	5.50
H1C-137	H1C-137-S	H1C-137-A	1 3/8	2 3/8	1/2	1/4-28 x 3/4	10	6.20
H1C-143	H1C-143-S	H1C-143-A	1 7/16	2 3/8	1/2	1/4-28 x 3/4	10	5.90
H1C-150	H1C-150-S	H1C-150-A	1 1/2	2 1/2	1/2	1/4-28 x 3/4	10	6.50
H1C-156	H1C-156-S	H1C-156-A	1 9/16	2 1/2	1/2	1/4-28 x 3/4	10	6.20
H1C-162	H1C-162-S	H1C-162-A	1 5/8	3	5/8	5/16-24 x 1	10	13.20
H1C-168	H1C-168-S	H1C-168-A	1 11/16	3	5/8	5/16-24 x 1	5	12.70
H1C-175	H1C-175-S	H1C-175-A	1 3/4	3	5/8	5/16-24 x 1	5	12.10
H1C-187	H1C-187-S	H1C-187-A	1 7/8	3 1/4	5/8	5/16-24 x 1	5	14.60
H1C-193	H1C-193-S	H1C-193-A	1 15/16	3 1/4	5/8	5/16-24 x 1	5	14.00
H1C-200	H1C-200-S	H1C-200-A	2	3 1/4	5/8	5/16-24 x 1	5	13.40
H1C-212	H1C-212-S		2 1/8	3 1/2	5/8	5/16-24 x 1	5	15.80
H1C-218	H1C-218-S		2 3/16	3 1/2	5/8	5/16-24 x 1	5	15.40
H1C-225	H1C-225-S		2 1/4	3 1/2	5/8	5/16-24 x 1	5	14.90
H1C-237	H1C-237-S		2 3/8	3 1/2	5/8	5/16-24 x 1	5	13.50
H1C-243	H1C-243-S		2 7/16	4	3/4	3/8-24 x 1	5	28.30
H1C-250	H1C-250-S		2 1/2	4	3/4	3/8-24 x 1	5	24.70
H1C-262	H1C-262-S		2 5/8	4 1/4	3/4	3/8-24 x 1	5	27.70
H1C-268	H1C-268-S		2 11/16	4 1/4	3/4	3/8-24 x 1	5	26.80
H1C-275	H1C-275-S		2 3/4	4 1/4	3/4	3/8-24 x 1	5	26.50
H1C-287	H1C-287-S		2 7/8	4 1/2	3/4	3/8-24 x 1	5	30.30
H1C-293	H1C-293-S		2 15/16	4 1/2	3/4	3/8-24 x 1	5	29.30
H1C-300	H1C-300-S		3	4 1/2	3/4	3/8-24 x 1	5	28.30
H1C-318	H1C-318-S		3 3/16	4 1/2	7/8	3/8-24 x 1	5	28.30
H1C-325	H1C-325-S		3 1/4	4 1/2	7/8	3/8-24 x 1	5	27.30
H1C-343	H1C-343-S		3 7/16	4 3/4	7/8	3/8-24 x 1	5	31.00
H1C-350	H1C-350-S		3 1/2	4 3/4	7/8	3/8-24 x 1	5	29.10
H1C-393	H1C-393-S		3 15/16	5 1/4	7/8	3/8-24 x 1	5	35.00
H1C-400	H1C-400-S		4	5 1/4	7/8	3/8-24 x 1	5	33.00

DIMENSION
Bore, Inch

TOLERANCE
+.003/- .000

* H1C-318 through H1C-400 do not have recessed screws.
 * Black oxide steel and aluminum bore sizes 3/4" through 3" do not have a relief cut.
 * Stainless steel bore sizes 1 9/16" through 3" do not have a relief cut.