## Short handle puller

## The CM Short Handle Puller is designed for easy operation, especially in hard to reach small spaces. It features:

- Easy one-hand operation
- Lever pull range is 45 to 62 pounds to lift full load
- Handle that rotates 360°, making it easy to operate in any position and in small spaces
- Tough yet lightweight aluminum construction and powder coat finish
- Hoistaloy hardened steel load chain for strength, long wear life and flexibility

- Free chaining for fast, easy attachment to load
- Forged upper and lower hooks with latches
- Simple construction with fewer parts for ease of maintenance
- Optional Load Limiter device
  protects against overload
- Lifetime warranty
- Made in U.S.A.



Rated capacity* (tons)	Product code	Standard lift (ft.)	Pull to lift full loads (lbs.)	Minimum distance between hooks (in.)	Lever length (in.)	Reeving	Hook throat openings (in.)	Approx. shipping weight (lbs.)
3⁄4	7300P	5	45	12 <sup>1</sup> /4	12	1	<b>1</b> <sup>1</sup> /32	16
<b>1</b> <sup>1</sup> /2	7320P	5	55	<b>1</b> 4 <sup>3</sup> ⁄4	16 <sup>3</sup> ⁄4	1	1 <sup>1</sup> ⁄8	27
3	7330P	5	62	17 <sup>5</sup> ⁄8	16 <sup>3</sup> ⁄4	2	<b>1</b> <sup>3</sup> ⁄16	40

Optional

Load Limiter

## Specifications -Short handle puller without chain

Rated capacity* (tons)	Product code	Approx. shipping weight (Ibs.)
3⁄4	7301P	12
1 <sup>1</sup> /2	7321P	21
3	7331P	28

## **Optional kits**

		Product code	Approx. shipping weight (lbs.)	Rated capacity* (tons)
Load Limiter		7310P	1	3/4
Load Limiter		7311P	2	1 <sup>1</sup> /2-3
Anchor Sling		7309P	2	3/4
Anenor oling		7312P	3	1 <sup>1</sup> /2
	upper	1001	2	3/4
		1003	2	1 <sup>1</sup> /2
Latchlok Hook		1004	3	3
Laternok Hook	lower	1001	2	3/4
		1003	2	1 <sup>1</sup> /2
		1005	3	3



Optional upper Latchlok Hook <sup>3</sup>/<sub>4</sub> – 1<sup>1</sup>/<sub>2</sub> ton



Optional upper Latchlok Hook 3 ton



Optional anchor sling