

DUAL PURPOSE HOSE REELS - AIR/ELECTRIC **C SERIES**

COXREELS® C Series "Combination" spring driven air hose/electric cord reels are two reels in one compact assembly. They are perfect for applications that require pneumatic air and an electrical power feed. The single expanded mounting base creates stability and adds to the convenience of one mounting pattern. This series is also available in dual hose combinations.


FOR INDOOR USE ONLY

Coxreels electric and pneumatic hose reels operate as two independent, self-retracting 50 foot trouble-free assemblies. All models rated: 115 volts, 3* conductors, 60 hz single phase.

HOSE & CORD											SIZE INDEX
MODEL	ACCESSORY	AWG / NO COND.	CORD FT.	TYPE	AMPS.	I.D.	O.D.	FT.	PSI	APRX. LBS.	
C-L350-5016-A	Single Industrial Receptacle†	16 / 3	50	SJO	13	3/8"	5/8"	50	300	94	1
C-L350-5012-A		12 / 3	50	SJO	20	3/8"	5/8"	50	300	96	
C-L350-5012-B	Quad "4 Plug" Industrial Receptacle† 	12 / 3	50	SJO	20	3/8"	5/8"	50	300	97	1
C-L350-5016-C	Fluorescent Tube Light - Shock Absorbing & Shatter Resistant† 	16 / 3	50	SJTO	.3	3/8"	5/8"	50	300	94	
C-L350-5016-D	Fluorescent Angle Light with Tool Tap Plug† 	16 / 3	50	SJTO	13	3/8"	5/8"	50	300	94	1
C-L350-5016-D2	Dual Fluorescent Angle Light with Tool Tap Plug† 	16 / 3	50	SJTO	12	3/8"	5/8"	50	300	94	
C-L350-5016-E	Incandescent Caged Drop Light with Tool Tap Plug† 	16 / 3	50	SJTO	13	3/8"	5/8"	50	300	94	1
C-L350-5016-F	Duplex G.F.C.I. Metal Industrial Receptacle†	16 / 3	50	SJO	13	3/8"	5/8"	50	300	94	
C-L350-5012-F		12 / 3	50	SJO	20	3/8"	5/8"	50	300	96	1
C-L350-5016-X	With Hose, With Cord, Less Accessory	16 / 3	50	SJO	13	3/8"	5/8"	50	300	93	
C-L350-5012-X		12 / 3	50	SJO	20	3/8"	5/8"	50	300	95	1
C-L350L-5016L-X	Less Hose, Less Cord, Less Accessory	16 / 3	50	N/A	25	3/8"	5/8"	50	300	78	
C-L350L-5012L-X		12 / 3	50	N/A	25	3/8"	5/8"	50	300	78	1

REEL DIMENSIONS Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	X	Y	M	N
1	16"	18 5/8"	17"	8"	9"	7"	8"



UL Listed† :: Accessories only **C SERIES :: REEL SPECIFICATIONS**

SWIVEL & LEAD CABLE

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE
- External CPC™ powder coated steel components cover for simple slip ring routine maintenance
- Include 5' lead cable & grounding plug (except on less cord models)

DESIGN & STRUCTURE

- Compact two reel assembly for air/electric applications, each reel operates independently
- Guide arm adjusts to wall, floor & overhead positions
- Single expanded, 1/4" steel mounting base for increased stability & space efficiency
- One mounting pattern allow 1/2 the installation time required to install 2 reels at one station
- 1" solid steel axle & lubricated precision bearings for smooth rotation

RETRACTION

- Enclosed factory tuned & matched cartridge-style spring motor
- Non corrosive stainless steel spring, pawl & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose/cord at desired length

SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Air Services
- Pneumatic Tools
- Power Tools
- Light Source
- General Industrial
- Manufacturing Plants & Facilities
- Maintenance, Repair & Operations
- Automotive & Fleet Service Centers

ACCESSORIZE YOUR REEL :: PG 50

- O-Rings & Swivels
- Mounting Brackets
- Hoses
- Assorted Reel Accessories

SPRING DRIVEN

