

DEMOLITION RECIPROCATING SAW BLADES

- Optimal blade height and blade thickness provides extreme durability
- Wider high speed steel strip for stronger teeth and longer wear
- Specially formulated anti-stick coating helps to minimize friction



BLADE SPECS
Height 1"
Thickness .050"/.062"
Matrix II Bi-Metal
.080" HSS Wire
Reinforced Teeth

Cat #	Length	TPI	Body Type	Milwaukee	Lenox	Starrett	Morse
5 Packs							
DW4862	6"	6	Taper	48-00-5021	20512-6066R	-	-
DW4863	9"	6	Taper	48-00-5026	20598-966R	-	-
DW4860	12"	6	Taper	48-00-5027	20500-106R	-	-
DW4864	6"	10	Straight	48-00-5712	20592-650R	-	RB6501014P
DW4865	9"	10	Straight	48-00-5713	-	-	RB8501014P
DW4866	6"	14	Straight	48-00-5782	20593-6514R	-	-
DW4868	9"	14	Straight	48-00-5787	20511-9514R	-	-
DW4867	6"	18	Straight	48-00-5784	20594-6518R	-	-
DW4869	9"	18	Straight	48-00-5788	-	-	-
25 Packs							
DW4863B25	9"	6	Taper	48-00-8026	20523-B966R	-	-
DW4865B25	9"	10	Straight	48-00-8713	-	-	-
100 Packs							
DW4863B	9"	6	Taper	-	-	-	-
DW4864B	6"	10	Straight	-	-	-	RB6501014B
DW4865B	9"	10	Straight	-	-	-	RB8501014B
DW4866B	6"	14	Straight	-	-	-	-
DW4868B	9"	14	Straight	-	-	-	-

MISCELLANEOUS RECIPROCATING SAW BLADES

Cat #	Length	TPI	Body Type	Milwaukee	Lenox	Starrett	Morse
5 Packs							
DW4814	3-1/2"	14	Scrolling	48-00-5162	20520-314RC	-	-
DW4815	3-1/2"	18	Scrolling	48-00-5163	20521-318RC	SB418-5	RB318SP
DW4816	6"	6	Scrolling	-	20521-676RC	-	RB65006CP
DW4851	6"	6	Drywall	48-00-5052	20570-636RP	VB66-5	RB606PP
DW4843	8"	Coarse	Carbide Grit	48-02-1430	-	-	-
DW4844	6"	Coarse	Carbide Grit	48-02-1420	-	-	-



DW4862
5 Pack



DW4814
5 Pack