

PRODUCT: | **E5650**
PURPOSE: | **DIGITAL BENCH TOP RECIPROCAL SHAKER**

Eberbach’s E5650 Digital Bench top Reciprocal Shaker is designed expressly to occupy a minimum of bench space while maintaining the high load capabilities Eberbach products are known for. The E5650 is a linear reciprocating shaker, it does not use the rocker arm suspension other Eberbach reciprocating shakers use, the E5650 uses a linear rail suspension system. The E5650 is a variable speed shaker designed for continuous duty. The speed is continuously variable between a range of 20 - 240 osc/min. The horizontal stroke is factory set at 1”. A 1.5” stroke model is also available. This reciprocal shaker model will shake a load of 40 lbs at low speed and 20 lbs at maximum. Its bench top footprint measures 21”x 15”. A digital controller controls platform speed and allows for timed operations. A stainless steel model E5650.SS and a incubator ready model E5650.IN are also available. Contact Eberbach for details.



Shown with optional E6040 box carrier

PRODUCT SPECIFICATIONS...

ROTATING SPEED:	20 - 240 osc/min
STROKE:	1” (Can be factory set up to 1.5”)
TYPE OF MOUNTING:	<ul style="list-style-type: none"> • Bench top • Suction cup feet to prevent creeping
LOAD CAPACITY:	Accepts loads up to 40 lbs at low speed 20 lbs at high speed
POWER REQUIREMENTS:	115V, 50/60Hz or 230V, 50/60Hz
POWER CONSUMPTION:	45 Watts
SIZE AND WEIGHT:	Length: 19.5”, Width: 14.5”, Height: 10” (with box carrier), Weight: 40 lbs
OPTIONS:	<ul style="list-style-type: none"> • Flask holders (E6090) can be mounted on an optional platform (E6061) • Utility box carrier (E6040) with rubber surface and one (1) rubber coated bar • Platform tiering post available for increased shaking capacity

DURABILITY • CRAFTSMANSHIP • QUALITY