

▼ Shown: Grip Puller Set BHP-351G



- Precise hydraulic control allows fast, efficient and safe pulling
- High quality, forged steel components provide superior reliability and service
- Available with and without full hydraulic set.

BHP Series



Capacity:

13, 22, 33 and 45 ton

Maximum Reach:

252 - 700 mm

Maximum Spread:

249 - 1100 mm

Maximum Operating Pressure:

700 bar

Ordering Example

Model Number BHP-251G:

includes Grip Puller BHP-252 and a full hydraulic set. (Hand pump, cylinder, saddle, hose, gauge and gauge adaptor).

Model Number BHP-252:

includes Grip Puller mechanical parts only, for use with your existing hydraulics.

▼ SELECTION CHART

Grip Puller Set Capacity **		13 ton	22 ton	33 ton	45 ton ***	
Model Number ►		BHP-152 ¹⁾	BHP-251G	BHP-351G	BHP-551G	
Included Hydraulics						
Set Weight ►		22 kg	56 kg	91 kg	160 kg	
• Hand Pump		P-142	P-392	P-392	P-80	
• Cylinder		RWH-121	RCH-202	RCH-302	RCH-603	
• Saddle		-	HP-2015	HP-3015	HP-5016	
• Hose		HB-7206QB	HC-7206	HC-7206	HC-7206	
• Gauge		GF-120P	GF-813P	GF-813P	GF-813P	
• Gauge Adaptor		GA-4	GA-3	GA-3	GA-3	
10	Grip Puller *	Model Number ►	BHP-1762 *	BHP-252 *	BHP-352 *	BHP-552 *
Maximum Spread (mm)		2-jaw	249	400	593	899
		3-jaw	249	499	800	1100
Maximum Reach (mm)		2-jaw	252	300	387	700
		3-jaw	252	300	387	700
Jaw (mm)		Thickness	15	20	24	30
		Width	23	27	38	39
Adjusting Screw (mm)		Thread	¾" - 16 UNF	1" - 8 UNC	1¼" - 7 UNC	1½" - 5.5 UNS
		Length	400	670	790	975
• Case			CW-166	CW-166	CW-350	CW-750

¹⁾ Includes Adaptor FZ-1630.

* Grip Puller order number without hydraulics.

** See warning on page 152.

*** Puller capacity at 540 bar; maximum cylinder capacity at 700 bar is 60 ton.