

▼ Shown from left to right: VC-20, VC-4L



## Remote Control of Single and Double-Acting Cylinders and Tools



### Locking Valves

For applications that require positive load holding, VC-Series valves are available with a pilot-operated check valve. This option provides hydraulic locking of the load until the valve is shifted into the retract position.

- Advance/Hold/Retract operation for use with single-acting or double-acting cylinders and tools.

Valve Operation	Used with Cylinder	Valve Type	Model Number	Hydraulic Symbol	Schematic Flowpath			Weight (kg)
					Advance	Neutral	Retract	
Manual	Single-Acting	3-Way, 3-Position, Tandem Center	<b>VC-3</b>					2,9
Manual	Single-Acting	3-Way, 3-Position, Tandem Center, Locking	<b>VC-3L</b>					4,7
Manual	Single-Acting	3-Way, 3-Position, Closed Center	<b>VC-15</b>					2,9
Manual	Single-Acting	3-Way, 3-Position, Closed Center, Locking	<b>VC-15L</b>					4,7
Manual	Double-Acting	4-Way, 3-Position, Tandem Center	<b>VC-4</b>					2,9
Manual	Double-Acting	4-Way, 3-Position, Tandem Center, Locking	<b>VC-4L</b>					4,7
Manual	Double-Acting	4-Way, 3-Position, Closed Center	<b>VC-20</b>					2,9
Manual	Double-Acting	4-Way, 3-Position, Closed Center, Locking	<b>VC-20L</b>					4,7

Return line kit included with remote valves.