It's simple. It's inline. It's much more.

Over the years, the inline fan has become an icon of the ultimate union of shape and function. Its performance suits almost any need, but a long life span is what truly makes it a must-have piece.



The Classic inline fan

FG Series is designed for installation in circular ducts for variaty of applications: from simple fresh air intake into residential dwellings to exhaust of stale air from basements and crawlspaces.

Airflow ranges between 110 and 950 cfm. Galvanized steel housing. 100% speed controllable. Speed controller sold separately

FG 4XL

20W, 135 cfm	72W, 170 cfm	73W, 220 cfm
7 lbs	8 lbs	8 lbs
FG 6 67W, 303 cfm 10 lbs	FG 6M 120W, 418 cfm 12 lbs	FG 6XL 153W, 483 cfm 12 lbs
FG 8	FG 8XL	FG 10
120W, 461 cfm	142W, 502 cfm	140W, 513 cfm
12 lbs	13 lbs	12 lbs
FG 10XL 195W, 589 cfm 14 lbs	FG 12 181W, 741 cfm 18 lbs	FG 12XL 277W, 940 cfm 21 lbs

See page 136 for full product specifications

Pair with controls and accessories



FG 4





FG 5XL

Speed Control



Iris Damper

Neither do we. That's why they never leak.

on these fans?

FG., EC Series offers same features as classic FG fans come standard equipped with a built-in potentiometer for "set-it and forget it" speed control. They are ideal for standard duct boosting where balancing the flow is critical.



FG 4XL EC 32W, 180 cfm

87W. 513 cfm

FG 10 EC

9 lbs

75W, 363 cfm

FG 6M EC

FG 12 EC 12 lbs

FG 12XL EC 120W, 633 cfm 162W, 805 cfm

69W, 428 cfm

16 lbs

FG 8 EC

9 lbs

Do you see any rivets

See page 137 for full product specifications.

Using this fan for exhaust?

Pair it with these accessories:



FG 4XL EC Inline Fan



Silencer

Wall Louver

We all know that rivets in fan housings leak air. Our manufacturing process guarantees that rivets aren't nessesary and ensures an air-tight seal. As a result, stale air leaves your home, not the fan.



