

T059/16V
€ 2110,00
GEARED DRILLING MILLING MACHINE

With variable speed

COMPATIBLE WITH STARTER KITS SKTF3B

| | |
|---|-------------------|
| Max drilling capacity on steel with pre-drilling hole(s235jr) | Ø 16 mm |
| Face milling cutter max | Ø 50 mm |
| End milling capacity | Ø 16 mm |
| Spindle taper | CM 2 |
| Chuck sizes | 1 - 13 mm B16 |
| Motor | 230 V 50 Hz 500 W |
| Net weight | 72 kg |


T058
€ 1700,00
GEARED DRILLING MILLING MACHINE

With variable speed

COMPATIBLE WITH STARTER KITS SKTF3F

| | |
|---|---------------------|
| Max drilling capacity on steel with pre-drilling hole(s235jr) | Ø 13 mm |
| Face milling cutter max | Ø 30 mm |
| End milling capacity | Ø 16 mm |
| Spindle taper | CM 3 |
| Motor | 230 V 50 Hz 0,55 kW |
| Net weight | 70 kg |


0857
€ 916,00
RADIAL FLOOR DRILL PRESS WITH DRIVE BELT

Rotating and tilting table with double arm, tilting head, electrical system with separate 24V circuit for on-board machine controls.

COMPATIBLE WITH STARTER KITS SKTEF E SKTEB

| | |
|---|----------------------|
| Max drilling capacity on cast iron with pre-drilling hole | Ø 20 mm |
| Max drilling capacity on steel with pre-drilling hole(s235jr) | Ø 16 mm |
| Continuous drilling capacity | Ø 12 mm |
| Chuck sizes | 1 - 16 mm B16 |
| Motor | 230 V 50 Hz 0,375 kW |
| Dimensions | 950 x 300 x 1600 mm |


0757
€ 700,00
RADIAL DRILL PRESS WITH DRIVE BELT

Rotating and tilting table with double arm, tilting head, electrical system with separate 24V circuit for on-board machine controls.

COMPATIBLE WITH STARTER KITS SKTEF E SKTEB

| | |
|---|----------------------|
| Max drilling capacity on cast iron with pre-drilling hole | Ø 20 mm |
| Max drilling capacity on steel with pre-drilling hole(s235jr) | Ø 16 mm |
| Continuous drilling capacity | Ø 12 mm |
| Chuck sizes | 2 - Ø 16 mm |
| Motor | 230 V 50 Hz 0,375 kW |
| Dimensions | 950 x 300 x 810 mm |


0754/230V
€ 1620,00
FLOOR DRILL PRESS WITH DRIVE BELT

Inclined table. Electrical system with separate 24V circuit for on-board machine controls.

COMPATIBLE WITH STARTER KITS SKTEF E SKTEB

| | |
|---|--------------------|
| Max drilling capacity on cast iron with pre-drilling hole | Ø 32 mm |
| Max drilling capacity on steel with pre-drilling hole(s235jr) | Ø 28 mm |
| Continuous drilling capacity | Ø 20 mm |
| Spindle taper | CM 4 |
| Motor | 230 V 50 Hz 1,5 kW |
| Net weight | 125 kg |


0754/400V
€ 1620,00
FLOOR DRILL PRESS WITH DRIVE BELT

Inclined table. Electrical system with separate 24V circuit for on-board machine controls.

COMPATIBLE WITH STARTER KITS SKTEF E SKTEB

| | |
|---|--------------------|
| Max drilling capacity on cast iron with pre-drilling hole | Ø 32 mm |
| Max drilling capacity on steel with pre-drilling hole(s235jr) | Ø 28 mm |
| Continuous drilling capacity | Ø 20 mm |
| Spindle taper | CM 4 |
| Motor | 400 V 50 Hz 1,5 kW |
| Net weight | 125 kg |


0752CM3
€ 1010,00
FLOOR DRILL PRESS WITH DRIVE BELT

Rotating and inclinable table. Electrical system with separate 24V circuit for on-board machine controls.

COMPATIBLE WITH STARTER KITS SKTEF E SKTEB

| | |
|---|---------------------|
| Max drilling capacity on cast iron with pre-drilling hole | Ø 25 mm |
| Max drilling capacity on steel with pre-drilling hole(s235jr) | Ø 20 mm |
| Continuous drilling capacity | Ø 16 mm |
| Motor | 230 V 50 Hz 0,75 kW |


0752
€ 947,00
FLOOR DRILL PRESS WITH DRIVE BELT

Rotating and inclinable table. Electrical system with separate 24V circuit for on-board machine controls.

COMPATIBLE WITH STARTER KITS SKTEF E SKTEB

| | |
|---|---------------------|
| Max drilling capacity on cast iron with pre-drilling hole | Ø 25 mm |
| Max drilling capacity on steel with pre-drilling hole(s235jr) | Ø 20 mm |
| Continuous drilling capacity | Ø 16 mm |
| Spindle taper | CM 2 |
| Motor | 230 V 50 Hz 0,75 kW |
| Net weight | 62 kg |

